Specifications

Eaton 116898

Catalog Number: 116898

Eaton Moeller series NZM - Molded Case Circuit Breaker. Main switch assembly kit, +additional handle red, size 2, NA type



General specifications

Product Name
Eaton Moeller series NZM operating element NA

Catalog Number
116898

EAN
4015081166381

Product Length/Depth
100 mm

Product Height
432 mm

Product Width
105 mm

Product Weight
0.806 kg

Compliances
UL/CSA
IEC
RoHS conform

Certifications
UL489
UL508A
NFPA79
UL listed
Specially designed for North America
CSA (File No. 22086)
CE marking
UL (Category Control Number DIHS)
CSA certified
IEC60947
CSA-C22.2 No. 5-09
CSA (Class No. 1437-01)
UL (File No. E140305)

Powering Business Worldwide

Product specifications

Used with

PN2(-4)
N(S)2(-4)
NZM2(-4)

Type

Accessory
Main switch assembly kit

Special features

External warning plate/designation label can be clipped on.
For enhanced busbar tag shroud on the incomer side, please order IP2X protection against contact with a finger.
Kit for use as a main switch

Features

With red door coupling rotary handle for use of switch as emergency switching off device
Lockable

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to

Resources

Brochures

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

eaton-digital-nzm-brochure-br013003en-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Declarations of conformity

DA-DC-03_NZM2

Drawings

eaton-circuit-breaker-switch-nzm-mccb-dimensions.eps

eaton-circuit-breaker-switch-nzm-mccb-3d-drawing-005.eps

Installation instructions

eaton-door-coupling-handle-north-america-variant-nzm2-xhb-il01206008z.pdf

Installation videos

Introduction of the new digital circuit breaker NZM

The new digital NZM Range

mCAD model

DA-CD-nzm2_xhb_da

DA-CS-nzm2_xhb_da

Technical data sheets

eaton-nzm-technical-information-sheet

normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Color

Red

Fitted with:

Add-on rotary handle on switch with "Deliberate Action" operation as per NFPA79 and UL508A Part 2
Black and yellow lightning symbol
Door coupling rotary handle with rotary drive
Extension shaft
External warning plate/marking plate in German/English
Padlock
Extension shaft NZM…-XV6 for mounting depth 600 mm

Frame

NZM2

Suitable for

Power circuit breaker
Emergency stop
Switch disconnector

Cover/door type

With activated door interlock. Cannot be opened in ON, OFF, or TRIP. Can only be opened in RESET.
Door interlock can be modified such that it can be defeated from the outside using a screwdriver
Door interlock not defeated in the locked OFF position.
Door interlock on OFF with max. 3 padlocks

Locking facility

Lockable on the 0 position on the handle using up to 3 padlocks
Lockable on the switch in the 0 position
Can also be modified in I position
With door interlock

Degree of protection / NEMA enclosure type

IP66
4X. 12

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia