Date: 12/04/2023

MWBXXUO - 0...16 mbar - 1/4 NPT-F - M20x1,5-F

Diaphragm pressure switch, Stainless steel case

Item number: 48705397

Quantity: 1 pcs.

Order code: MWBXXUO-MAFSC-1EMZZZZ1ZZZZZZZZZZZZZZZZZZZ ZCK1BW
M000300DZZZZZZZZ
F4-C1- - - - -

Overview:
MWBXXUO - 0...16 mbar - 1/4 NPT-F - M20x1,5-F
Diaphragm pressure switch, Stainless steel case
measuring elements and wetted materials: Diaphragm AISI 316, 304, Inconel or Hastelloy (Piston AISI 316)/ Process Connection AISI 316L
Contact version: 1x SPDT gold-plated contact, hermetically sealed, argon gas filling
setting range: 0...16 mbar
Standard, working range = 0...16 mbar, proof pressure 250 mbar
Process connection: 1/4 NPT-F
Electrical connection: M20x1,5-F
Enclosure with plate for wall or direct mounting
Ingress Protection: IP66
Diaphragm: Stainless Steel AISI 316/O-Ring: PTFE/Connection: Stainless steel AISI 316L
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 31.10
Repeatability of set point: ≤ 1% of span

Set point definition: Set Point customer-specifically configured
1. set point: 3.00 mbar decreasing,

Approvals / Certificates
IECEx-ATEX Ex ia

Details:
Diaphragm pressure switch, Stainless steel case
Model MW
Specifications according to data sheet: PV 31.10
Repeatability of set point: ≤ 1% of span
Contact version: 1x SPDT gold-plated contact, hermetically sealed, argon gas filling
setting range: 0...16 mbar
working range: Standard, working range = 0...16 mbar, proof pressure 250 mbar
Set Point customer-specifically configured
Unit: mbar
Process connection: 1/4 NPT-F
Electrical connection: M20x1,5-F
Enclosure with plate for wall or direct mounting
Brand: WIKA Instruments Italia

© 2023 - WIKA Instruments s.a.r.l.

Ingress Protection: IP66
MWBXXUO
Diaphragm: Stainless Steel AISI 316/O-Ring: PTFE/Connection: Stainless steel AISI 316L
1. set point: 3.00 mbar decreasing,

Approvals / Certificates
IECEx-ATEX Ex ia

© 2023 - WIKA Instruments s.a.r.l.