# ADXT023024

SOFT STARTER, ADXT… SERIES, FOR STANDARD AND HEAVY-DUTY APPLICATIONS, WITH BUILT-IN BYPASS RELAY. AUXILIARY SUPPLY VOLTAGE 24VAC/DC. RATED OPERATIONAL VOLTAGE 380...690VAC, 230A



| | | | |
|---|---|---|---|
| Product designation | | | Soft Starter |
| Product type designation | | | ADXT |
| Motor type | | | Asynchronous three phase |
| **Electrical features** | | | |
| Supplies voltage | | | |
| | Type of system | | Three phase |
| | Rated supply voltage | V | 380…690VAC |
| | auxiliary supply voltage (Us) | | 24VAC/DC |
| | Rated frequency | Hz | 50/60 |
| Rated starter current Ie | | A | 230 |
| Rated motor power in-line | | | |
| IEC ratings (T≤40°C) | | | |
| | 400VAC | kW | 132 |
| | 500VAC | KW | 160 |
| | 690VAC | KW | 200 |
| UL ratings (T≤40°C) | | | |
| | 380-415VAC | HP | 125 |
| | 440-480VAC | HP | 150 |
| | 550-600VAC | HP | 200 |
| Rated motor power inside delta | | | |
| IEC ratings (T≤40°C) | | | |
| | 400VAC | kW | 160 |
| | 500VAC | KW | 250 |
| | 690VAC | KW | 315 |
| UL ratings (T≤40°C) | | | |
| | 380-415VAC | HP | 200 |
| | 440-480VAC | HP | 250 |
| | 550-600VAC | HP | 350 |
| Number of controlled phases | | Nr. | 3 |
| Built-in bypass | | | Yes |
| Cooling System | | | Forced |
| Rated insulation voltage Ui | | V | 690 |
| **Programming interface** | | | |
| Display | | | LCD graphic display |
| Programming with NFC technology | | | No |
| Optical port | | | No |
| **Startup and stop settings** | | | |
| Startup method | | | Constant current, current ramp, voltage ramp, adaptive control |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

| | |
|---|---|
| Stop method | Voltage ramp, adaptive control, free-wheel stop, DC braking, soft stop with braking contactor |
| **Protections** | |
| Auxiliary supply protection | Voltage too low |
| Power supply Protection | No power, phase loss, phase sequence, frequency out of limits, voltage out of limits |
| Motor protection | Overload, locked rotor, current asymmetry, current too low, power too low, overtemperature, starting too long |
| Starter protection | Overcurrent, overtemperature, phase shorted |
| **Functions** | |
| Built-in bypass | Yes |
| Built-in display and keypad | Yes |
| Languages | 6 |
| View measurements | Yes |
| Torque control | No |
| Adjustable current limit | Yes |
| Dynamic braking | Yes |
| Kick Start function | Yes |
| Motor overload electronic protection | Yes |
| Motor protection PTC input | Thermistor input |
| Protection against phase loss | Yes |
| Protection against phase inversion | Yes |
| Protection against locked rotor | Yes |
| Protection against thyristor overtemperature | Yes |
| Protection against low load | Yes |
| Programmable alarm | Yes |
| Digital inputs | 4 |
| Analog inputs | 0 |
| Digital outputs | 3 |
| Analog output | 1 |
| Optical port for programming | No |
| Event log | Yes |
| Motor hour counter | Yes |
| Startup counter | Yes |
| Clock calendar | Yes |
| Remote external keypad | Yes |
| **Input and Output** | |
| Digital inputs | |
| Number of digital input | Nr. 4 |



The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

| | | | | |
|---|---|---|---|---|
| | | Digital input type | | 4 input with dry contact + 1 thermistor input |
| | | Digital input functions | | 1x Start/Stop, 1x Reset and 2 Programmable |
| Digital outputs | | | | |
| | | Number of digital output | Nr. | 3 |
| | | Digital output arrangement | | 2x 1NO + 1x C/O |
| | | Digital output functions | | 1NO Line contactor + 1NO Programmable + 1C/O Programmable |
| **Ambient conditions** | | | | |
| Temperature | | | | |
| | Operating temperature | | | |
| | | min | °C | -10 |
| | | max | °C | +60°C (with current derating >40°C) |
| | Storage temperature | | | |
| | | min | °C | -25 |
| | | max | °C | +60 |
| Max altitude | | | m | 1000 without derating |
| Relative humidity | | | % | <95% |
| Pollution degree | | | | 3 |
| **Housing** | | | | |
| Mounting | | | | Screw-fixing |
| IP degree of protection | | | | IP00 |
| Dimensions (W x H x D) | | | mm | 216x495x244 |
| Weight | | | Kg | 12.7 |
| **Dimensions** | | | | |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

# ADXT023024

SOFT STARTER, ADXT… SERIES, FOR STANDARD AND HEAVY-DUTY APPLICATIONS, WITH BUILT-IN BYPASS RELAY. AUXILIARY SUPPLY VOLTAGE 24VAC/DC. RATED OPERATIONAL VOLTAGE 380...690VAC, 230A




## Certifications and compliance

Compliance

| |
|---|
| CSA C22.2 n°60947-4-2 |
| IEC/EN/BS 60947-4-2 |
| UL 60947-4-2 |

Certificates

| |
|---|
| cULus |
| RCM |

## ETIM classification

| | |
|---|---|
| ETIM 8.0 | EC000640 - Soft starter |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding