Date: 12/04/2023

RLS-1000; Guide tube length: 450 mm; 1 switching output

RLS-1000; Guide tube length: 450 mm; 1 switching output

Item number: 48771984

Quantity: 1 pcs.

Order code: RLS-10003M304000ZZZZZZZZZZZZZZZZZZZ1CZ8M045004Z4
Z1W101ARS1ZL4

Overview:
RLS-1000; Guide tube length: 450 mm; 1 switching output
Magnetic float switch, Stainless steel version Model RLS-1000
Output Signal: 1 switching output
max. switching power: n.o./n.c.: AC 100 V; 10 VA; 0,5 A / DC 100 V; 10 W; 0,5 A
max. switching power: Changeover/SPDT: AC 100 V; 5 VA; 0,25 A / DC 100 V; 5 W; 0,25 A
Unit of measure switching position: mm
Switching function - Switch output 1 : changeover / SPDT
Switch position - Switch output 1 : 400 mm
Electrical connection: Angular connector DIN 175301-803 A, IP65
pin assignment el. connection: see product label
Process connection: G 1, installation from outside
Guide tube length: 450 mm mm
medium temperature: -30 °C ... 80 °C
Wetted parts: Stainless steel 1.4571
Float: Cylindrical float Ø 25 mm, Buna/NBR PN16
Specifications according to data sheet: LM 50.03

Details:
RLS-1000; Guide tube length: 450 mm; 1 switching output
Magnetic float switch, Stainless steel version Model RLS-1000
Output Signal: 1 switching output
max. switching power: n.o./n.c.: AC 100 V; 10 VA; 0,5 A / DC 100 V; 10 W; 0,5 A
max. switching power: Changeover/SPDT: AC 100 V; 5 VA; 0,25 A / DC 100 V; 5 W; 0,25 A
Unit of measure switching position: mm
Switching function - Switch output 1 : changeover / SPDT
Switch position - Switch output 1 : 400 mm
Electrical connection: Angular connector DIN 175301-803 A, IP65
pin assignment el. connection: see product label
Process connection: G 1, installation from outside
Guide tube length: 450 mm mm
medium temperature: -30 °C ... 80 °C
Wetted parts: Stainless steel 1.4571
Float: Cylindrical float Ø 25 mm, Buna/NBR PN16
Specifications according to data sheet: LM 50.03

© 2023 - WIKA Instruments s.a.r.l.