# DATASHEET - IZMX-SH404-1

**Shutter for withdrawable unit IZMX404**

| | |
|---|---|
| **Part no.** | **IZMX-SH404-1** |
| | **184193** |
| **EL Number (Norway)** | **4398536** |

| | |
|---|---|
| **General specifications** | |
| Product name | Eaton Moeller series IZMX/INX shutter |
| Part no. | IZMX-SH404-1 |
| EAN | 4015081783618 |
| Product Length/Depth | 350 millimetre |
| Product height | 50 millimetre |
| Product width | 250 millimetre |
| Product weight | 0.65 kilogram |
| Compliances | RoHS conform |
| Product Tradename | IZMX/INX |
| Product Type | Accessories |
| Product Sub Type | Shutter |
| **Delivery program** | |
| Type | Accessory |
| Number of poles | Four-pole |
| Nominal current | 4000 A |
| Features | Version as built-in device |
| Special features | For withdrawable unit<br>When the breaker is withdrawn from its connected position, the shutters automatically cover the cassette's live main terminals. |
| Used with | IZMX-CAS404…<br>Four-pole |
| **Technical Data - Electrical** | |
| Electrical connection type of main circuit | Other |
| **Technical Data - Mechanical** | |
| Mounting Method | Withdrawable |
| **Design verification as per IEC/EN 61439 - technical data** | |
| Ambient operating temperature - min | -25 °C |
| Ambient operating temperature - max | 70 °C |
| **Additional information** | |
| Accessory/spare part type | Withdrawable units |

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Chassis part power circuit breaker (EC002043)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Chassis part circuit breaker (ecl@ss13-27-37-04-22 [ACN955016])

| | | |
|---|---|---|
| Rated current In | A | 4000 |
| Number of poles | | 4 |
| Version as busbar adapter | | No |
| Version as built-in device | | Yes |
| Type of electrical connection of main circuit | | Other |


© 04/2023 by Eaton Industries GmbH