Date: 23/01/2024

A5500/1, NS100, 0...500°C, L1=290x8mm

A 5501/1 100 mm Inox 316 500 °

Item number:	3908240
Quantity:	1 pcs.
Order code:	A5500 -1-C1S-BK-C290GZZ-ZZZZZZ TB FZZZEPZSVID-AZ1ZZZZZ2ZZZZ
Overview:	A5500/1, NS100, 0...500°C, L1=290x8mm Process connection: plain, without thread, axial flat instrument glass, class 1 per EN 13190 with Serial number *WIKA*
Details:	A 5501/1 100 mm Inox 316 500 ° TEMPERATUR A 5501/1 NG 100 CrNi-Stahl 1.4401 500 °C L1=280x8mm Klasse 1 (nach Din 16203) Bimetallwendel Instrumentenflac Bimetall-Thermometer, Chemieausführung Typ: A 5500, Nenngröße 100, Anschlusslage rückseitig (axial) Technische Daten nach Datenblatt: TM 55.01 Genauigkeitsklasse: Kl. 1 nach EN 13190 (Ersatz für DIN 16203) Gehäuse: CrNi-Stahl Tauchschaftwerkstoff: CrNi-S Bimetal thermometer, stainless steel version Specifications according to data sheet: TM 55.01 Case: stainless steel Stem material: stainless steel Model: A 5500, nominal size 100, location of stem centre back (axial) Connection design: 1, plain stem Unit: °C Scale range: 0 °C ... 500 °C Process connection: plain, without thread Stem diameter: 8 mm Insertion length L1: 290 mm Window: flat instrument glass Case: Stainless steel Connector location: axial Version: standard Stem material: stainless steel Permissible ambient temperature: -40 ... +70 °C Manufacturer logo: *WIKA* Accuracy class: class 1 per EN 13190 Ingress protection: IP 65 Serial number: with Serial number

© 2024 - WIKA Instruments s.a.r.l.