PPS SQ SYSTEM 100% ALUMINIUM NETWORK

PPS SQO9C - Tapping flange with double outlet for square profile-



Made of black aluminum treated by cataphoresis, the 90° equal aluminum elbow ensures quick installation, optimal reliability, and high resistance in industrial environments. Connected to the square profile, it guarantees the flow both directly and at 90°.

COMPACT, LIGHT AND EASY TO ASSEMBLY.

Transmission of always clean and high-quality air

PRESSURE DROPS ARE VERY LOW THANKS TO A SMOOTH INTERNAL SURFACE, A LOW FRICTION COEFFICIENT, AND A MAXIMUM PASSAGE DIAMETER, THUS ENSURING OPTIMIZED FLOW RATES

100% aluminium
Ergonomics of workstations
Space saving
Modularity
Quality & Safety
Watertightness guaranteed
User comfort

IT IS AN IDEAL SOLUTION DESIGNED TO MEET THE RIGOROUS DEMANDS OF MODERN INDUSTRY, ENSURING RELIABLE AND EFFICIENT OPERATION ACROSS DIVERSE SECTORS.

The PPS SQ solution offers modular and scalable configurations, specific for end-uses of a piping network ,where in most cases it is necessary to fit to different work stations

Part number	Material	Female thread	For pipe OD	Temperature min/ max (°C)	Max. operating pressure	Net weight (Kg)
PPS SQO9C2512	Aluminium	G1/2	25 mm	-20.00 / 80.00	16.00	0

Prevost SAS - 15, rue du Pré Faucon - CS 90208 - Annecy-le-Vieux - 74940 Annecy - France
Tél. +33 (0)4 50 64 04 45 - sales@prevost.eu - www.prevost.eu