Rittal – The System.

Faster – better – everywhere.



DK 7072.240

Nylon loop

State: 1/2/2023 (Source: rittal.com/in-en)

DK 7072.240 - Nylon loop

With the nylon loop, secured cables are easily released, allowing individual cables to be added or removed, ideal for sensitive data cables (fibre-optic/Cu).

Features

Model No.	DK 7072.240
Product description	With the nylon loop, secured cables are easily released, allowing individual cables to be added or removed. Ideal for sensitive data cables (fibre-optic/Cu), as it avoids indentations on the cable sheathing. In addition, the nylon loop may be screw-fastened to the round system punchings or attached using a quick-release fastener.
Colour	Black
Supply includes	Quick-release fastener
Dimensions	Width: 20 mm Length: 300 mm
Max. cable diameter	90 mm
Packs of	10 pc(s).
Weight/pack	0.05 kg
Copper weight (kg per piece)	0
Customs tariff number	39191019
EAN	4028177147911
ETIM 7.0	EC002625
ECLASS 8.0	27189234

Approvals

Approvals	GOST

Tender text

Nylon loop for cable routing, max. cable diameter 90 mm

The nylon loop is attached to cable clamp rails, C rails, system rails or to the enclosure frame. The nylon loop may be screw-fastened as per the 25 mm DIN pitch pattern. The nylon loop can hold cable bunches up to 90 mm in diameter; single cables can easily be added or detached.
Nylon loop length: 300 mm
Max. cable diameter: 90 mm

Packs of 1

© Rittal 2023