Rittal – The System.

Faster – better – everywhere.

Polycarbonate enclosures PK without knockouts – PK 9523.100

Date : Apr 27, 2021

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Polycarbonate enclosures PK without knockouts – PK 9523.100

created: 27.04.2021 build on www.rittal.com/uk-en



Product description

Applications:	Ambient temperature range: -35 °C...+80 °C The specified temperatures may be limited by the installed equipment
Material:	Enclosure: Fibreglass-reinforced polycarbonate Cover transparent: Polycarbonate, all-round foamed-in PU seal Cover screws: Polyamide Insulating bungs: Polyethylene
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4X
IK Code:	IK08
Supply includes:	Enclosure with cover Cover screws Insulating bungs for wall mounting screws
Basic material:	Polycarbonate

Product description

Dimensions:	Width: 360 mm Height: 254 mm Depth: 111 mm

Cover:	transparent
Ambient temperature range:	-35 °C...+80 °C
Packs of:	1 pc(s).
Weight/pack:	1.5 kg
EAN:	4028177139879
Customs tariff number:	94037000
ETIM 7.0:	EC000261
ETIM 6.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 6.0/6.1:	27180101
Product description:	PK Polycarbonate enclosure, WHD: 360x254x111 mm, fibreglass-reinforced polycarbonate, without knockouts, with transparent cover

Approvals

Approvals:	C-UL DNV-GL UL
Certificates:	NA
Declarations:	Declaration of conformity