Brand of NTN Group

Technical data


UC214-44G2

Insert bearings



Spherical outer diameter, fixing by socket set screw, seal with slinger

VISUAL (S)



PRODUCT DEFINITION

Brand	SNR
B - Width of Inner Ring	74,6 mm
C - Width of Outer Ring	30 mm
C1 - Distance center of OR to center of lubrication zone	9 mm
d - Shaft diameter	69,85 mm
D - Outer diameter of OR	125 mm
G - Set screw size	7/16-20UNF
m - Distance to set screw	12 mm

UC214-44G2
Insert bearings

PRODUCT DEFINITION	
r - Radius Inner Ring	2
S - Distance front side/bearing centre	30,2 mm
f0 - Factor	14.4
SW - Wrench size	5,556 mm

PRODUCT PERFORMANCE	
C - Dynamic load rating	62000000 mN
C0 - Static load rating	45000000 mN
Operating temperature min.	253,15 °K
Operating temperature max.	373,15 °K

OTHER FEATURES	
Mass	2,06 kg
Recommended tightening torque for set screw	27.1 N-m

BEARING FREQUENCIES	
BPFO - Over rolling frequency on outer ring (60 rpm)	4.10448717948718 Hz
BPFI - Over rolling frequency on inner (60 rpm)	5.89551282051282 Hz
BSF - Over rolling frequency on rolling element (60 rpm)	5.40429042086522 Hz
BRF - Rotational frequency – rolling element (60 rpm)	2.70214521043261 Hz
FTF - Rotational frequency - cage (60 rpm)	0.410448717948718 Hz