EMPTY ENCLOSURE

AKL 2-t



AKL 2-t

Empty enclosure

CUSTOMIZABLE

300 x 300 x 132 mm
Article number: 74400201

Empty enclosure, with attachment bushes, sealing and insulating plugs, base: polystyrene, grey similar to RAL 7035, cover: polycarbonate, transparent

IP65 IK07 690V AC 1000V DC

Technical data

Measures

Width:	300 mm
Length:	300 mm
Height:	132 mm
Inner height:	114 mm

Material

Base:	Polystyrene, grey, similar to RAL 7035
Cover:	Polycarbonate, transparent
Sealing:	Polyurethane
Cover screw:	Polyamide 6, fiber-glass reinforced

Other attributes

Ingress protection:	IP65 - acc. EN

Accessory

- AK MPI 2
- AK NS35-250
- NS35-216/3
- AK ABL-ES
- ASS-gro
- AK ABF 2
- AK TW

Günther Spelsberg GmbH + Co. KG · Im Gewerbepark 1 · D-58579 Schalksmühle · Germany · Phone: +49 (0) 23 55 / 892-0 · Fax: +49 (0) 23 55 / 892-299

EMPTY ENCLOSURE

AKL 2-t

	60529 / DIN VDE 0470-1
Impact restistance:	IK07 acc. DIN EN 5012 / VDE 0470 Part 100
Rated insulation voltage AC:	690 V V
Rated insulation voltage DC:	1000 V
PVC-free:	Yes
Heavy metals-free:	Yes
Silicone-free:	Yes
Combustion behaviour to UL:	HB acc. UL94
Combustion behaviour to VDE:	650°C acc. VDE 0471/ EN 60695
Knockouts:	Yes
sealable:	Yes

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%

Günther Spelsberg GmbH + Co. KG · Im Gewerbepark 1 · D-58579 Schalksmühle · Germany · Phone: +49 (0) 23 55 / 892-0 · Fax: +49 (0) 23 55 / 892-299