POLYAMIDE (PA) FLEXIBLE TUBING

Email Print



Tried-and-tested for industrial or vehicle applications, PA tubing guarantees excellent durability due to its stable long-term mechanical properties.
Special grade of semi-rigid polyamide manufactured according to our Eco-Design approach.

PART NUMBER:
1100P10 01

TUBING MATERIAL:
PA

TUBE I.D. (MM):
8

TUBE O.D. (MM):
10

COLOR:
BLACK

LENGTH (M):
100

Reset Attributes

WHERE TO BUY

PRODUCT OVERVIEW -

TECH SPECIFICATIONS +

Print Tech Specifications

PERFORMANCE CHARACTERISTICS

MAXIMUM PRESSURE (BARG)

50

MINIMUM WORKING TEMPERATURE (°C)

-40

MAXIMUM WORKING TEMPERATURE (C)

100

VACUUM RATING (MM OF HG)

755

WEIGHT (KG/PACKAGE)

3.4

MAXIMUM BEND RADIUS (MM)

50

NUMBER OF TUBES

1

APPLICATION

Packaging, Tooling, Compressed Air, Motion Technologies, Robotics, Industrial Machinery

MEDIA

Semi-Rigid PA: Compressed air, other fluids /Rigid PA: Compressed air,lubricants, other fluids

CERTIFICATES

Industrial: DI: 2002/95/EC (RoHS), 2011/65/EC; DI: 97/23/EC (PED); RG: 1907/2006 (REACH)/Transportation: Chemical performance and resistance tested according to DIN 74324 -1 / DIN 73378 / ISO 7724

Print Tech Specifications

PRODUCT SUPPORT +

RECOMMENDED


lencers


Stainless Steel Non-Return Valves


Pneumatic Sensor Fittings


Pneumatic Pilotec Non-Return Valve

CONTACT US

Parker Hannifin Manufacturing France SAS

Fluid System Connectors Division Europe
Parc Alcyone - Bat. D
1 rue André et Yvonne Meynier - CS 46911
35069 Rennes Cedex France

Phone
Phone: +33 (0) 2-99-25-55-00

EMAIL PARKER

Parker Hannifin +

Products
About Parker
Investors
Community
Careers

Global Operations +

Divisions
Sales Companies
Worldwide Locations
Distribution Network
ParkerStore™ Network

Company Information +