# DM2TA0300

Current transformer, split-core, 80X80mm hole, 300A



| | | | |
|---|---|---|---|
| Product designation | | | Current trasformers |
| Product type designation | | | DM2TA0300 |
| **Auxiliary supply Us** | | | |
| Operational frequency | | | |
| | min | Hz | 50 |
| | max | Hz | 60 |
| **Current inputs** | | | |
| Primary current Ipn (/5) | | A | 300 |
| Secondary output current | | A | 5 |
| Overload withstand Ipn | | % | 120 |
| Burden | | | |
| | cl. 0.5 | VA | 1.5 |
| | cl. 1 | VA | 3 |
| **Insulations** | | | |
| Rated insulation voltage Ui IEC/EN | | V | 720 |
| IEC rated short-time thermal current Ith | | Ith for s | 40…60 |
| IEC rated dynamic current Idyn | | Ith for s | 2.5 |
| Insulation dry type | | | Class E |
| **Mechanical features** | | | |
| Terminals type | | | Screw |
| Fixing | | | Screw fixing |
| Weight | | g | 1050 |
| **Ambient conditions** | | | |
| Temperature | | | |
| Operating temperature | | | |
| | min | °C | -25 |
| | max | °C | +50 |
| Storage temperature | | | |
| | min | °C | -40 |
| | max | °C | +80 |
| Relative humidity | | % | 90 |
| Protection degree | | | IP30 |
| **Dimensions** | | | |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

# DM2TA0300

Current transformer, split-core, 80X80mm hole, 300A




## Certifications and compliance

Compliance

IEC/EN 60044-1

Certificates

EAC

GOST

## ETIM classification

ETIM 8.0

EC002048 - Current transformer


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding