C-251 HV/LV/HVE CHARGER

WITHOUT COMPROMISE

PRODUCT INFORMATION

C-251 HV/LV/HVE chargers are for use with the Wolflite H-251MK2, H-251A and H-251ALED rechargeable Handlamps.

Simple setup and attachment to handlamp



FEATURES

- Single power source
- Quick and easy setup
- Quick release handlamp mechanism so handlamp is always ready for use
- HV / LV options available

TECHNICAL INFORMATION

C-251 CHARGER		
PRODUCT REFERENCE	**C-251 LV**	**C-251HV**
PRODUCT DESCRIPTION	Low Voltage Handlamp Charger	Mains Voltage Handlamp Charger
APPARATUS STANDARDS	-	LVD EN 60 335
INSULATION CLASS	III	II
ENCLOSURE	Polypropylene	
INPUT VOLTAGE	12-32Vdc	120/230Vac*
RECHARGE TIME	10-12 hrs at 24v	8-10 hrs
INGRESS PROTECTION	IP20	
WEIGHT (WITHOUT HANDLAMPS)	0.5kg	0.75kg
MOUNTING	All chargers may be bench or wall mounted	
COMPATIBLE HANDLAMP	H-251MK2 / H-251A / H-251ALED	

All information has been gathered under laboratory conditions, the user must regard the values given as approximate. Changes may be made to the above specification without notification, details are available on request.

- C-251 HV is also available with a European 2-Pin plug - Model No. C-251HVE
- *C-251 HV may also be powered from 'rig' voltage 254Vac 60 Hz

Wolf Safety Lamp Company
Saxon Road Works, Sheffield S8 0YA, UK

T: +44 (0) 114 255 1051
E: info@wolfsafety.com