Product data sheet
Characteristics

XS7G12MA230
Inductive proximity sensors XS, inductive sensor XS7 12x40x26, plastic, Sn2mm, 24...240VAC/DC, cable 2 m



Main

Range of product	Telemecanique Inductive proximity sensors XS
Series name	General purpose
Sensor type	Inductive proximity sensor
Product specific application	-
Sensor name	XS7
Sensor design	Form 12 x 40 x 26
Size	26 mm
Body type	Fixed
Enclosure material	Plastic
Type of output signal	Discrete
Wiring technique	2-wire
[Sn] nominal sensing distance	2 Mm
Discrete output function	1 NO
Electrical connection	Cable
Cable length	2 M
Wire insulation material	PVC
[Us] rated supply voltage	24...210 V DC 24...240 V AC 50/60 Hz
Switching capacity in mA	5...200 mA
IP degree of protection	IP67 conforming to IEC 60529

Complementary

Detection face	Lateral
Detector flush mounting acceptance	Flush mountable
Material	Plastic
Front material	Plastic
Operating zone	0…1.6 Mm
Differential travel	3...20% of Sr
Repeat accuracy	<= 10% of Sr
Output circuit type	AC/DC
Cable composition	2 x 0.34 mm²
Status LED	Output state: 1 LED (yellow)
Supply voltage limits	20…264 V AC/DC

mation provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
mentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
uty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
chneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Switching frequency	<= 25 Hz AC <= 250 Hz DC
Maximum voltage drop	<5.5 V (closed)
Maximum delay first up	40 Ms
Maximum delay response	1 Ms
Maximum delay recovery	2 Ms
Marking	CE
Depth	26 Mm
Height	40 Mm
Width	12 Mm
Net weight	0.1 Kg

Environment

Product certifications	CSA CCC UL
Ambient air temperature for operation	-25…70 °C
Ambient air temperature for storage	-40…85 °C
Vibration resistance	25 gn amplitude = +/- 2 mm (f = 10…55 Hz) conforming to IEC 60068-2-6
Shock resistance	50 gn for 11 ms conforming to IEC 60068-2-27

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	90.0 G
Package 1 Height	4.5 Cm
Package 1 width	4.5 Cm
Package 1 Length	14 Cm
Unit Type of Package 2	S02
Number of Units in Package 2	28
Package 2 Weight	2.896 Kg
Package 2 Height	15 Cm
Package 2 width	30 Cm
Package 2 Length	40 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months

Product Life Status : Commercialised