Date: 24/04/2023

232.30.100 1000 bar G1/2B lower mount

Bourdon Tube Pressure Gauges, Safety Pattern

Item number:	57306034
Quantity:	1 pcs.
Order code:	232.30-E-BG610Z-GD-UZHZCZZ-ZZZZZZZ 213D31ZI3W0 12Z-IZZZZZZ12ZZZ LABEL-PG1DE-ZZZZZ
Overview:	232.30.100 1000 bar G1/2B lower mount Measuring System 316L Ingress protection: IP 65 class 1.0 Window: laminated safety glass Permissible medium temperature: + 200 °C Permissible ambient temperature: -40 … +60 °C with thread protection Pressure Gauge Standard: International (standard Europe) *WIKA* with Serial number Label: WIKA standard without / with Tag-number
Details:	Bourdon Tube Pressure Gauges, Safety Pattern Series EN 837-1 Model: 232.30 Specifications according to data sheet: PM 02.04 Measuring system: stainless steel Case filling: without Nominal size: 100 mm Measuring range: gauge pressure range Scale range: 0...1000 bar Process connection: G 1/2 B Connector location: lower mount Window: laminated safety glass Pointer: standard pointer Accuracy class: class 1.0 Material pressure element: Measuring System 316L Thread protection: with thread protection Pressure Gauge Standard: International (standard Europe) Manufacturer logo: *WIKA* Bourdon Tube Pressure Gauges, Safety Pattern Series EN 837-1 Model: 232.30 Specifications according to data sheet: PM 02.04 Measuring system: stainless steel Case filling: without

© 2023 - WIKA Instruments s.a.r.l.

Nominal size: 100 mm
Measuring range: gauge pressure range
Scale range: 0...1000 bar
Process connection: G 1/2 B
Connector location: lower mount
Window: laminated safety glass
Pointer: standard pointer
Accuracy class: class 1.0
Overpressure safe: standard
Case material: Stainless steel 1.4301
Case surface: bare
Material pressure element: Measuring System 316L
Case filling fluid: prepared for filling
Ingress protection: IP 65
Permissible medium temperature: + 200 °C
Permissible ambient temperature: -40 … +60 °C
Movement: stainless steel
Thread protection: with thread protection
Packaging: single packing
Pressure Gauge Standard: International (standard Europe)
Manufacturer logo: *WIKA*
with Serial number
Permissible ambient temperature: -40 … +60 °C

© 2023 - WIKA Instruments s.a.r.l.