EPIC® MH 8

High flexibility by the use of any combination of inserts in one connector

Info
Modular connector system, plugable with the market standard
Module 8 pole for control signals



Voltage

Wind Energy

Rail

Mechanical and plant engineering

Kompletterande automationskomponenter från Lapp

Flame-retardant

Benefits
Module 8 pole for control signals
Crimp connection for permanent vibration proof contact
EPIC® MH system is mateable with the market standard
The mix of different functions in one plug guarantees high flexibility
Railway applications
- Fire protection on railway vehicles: Test according EN 45545-2. Requirement sets R22 and R23. Hazard level HL1, HL2 and HL3

Last Update (13.11.2018)
©2018 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

EPIC® MH 8

Application range

Mechanical engineering
Robotics industry
Plant engineering
Renewable energy
Railway applications / vehicle construction

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC002641 ETIM 5.0 Class-Description: Modular connector (industrial connector)
Classification ETIM 6:	ETIM 6.0 Class-ID: EC002641 ETIM 6.0 Class-Description: Modular connector (industrial connector)
Rated voltage (V):	400 V
Rated impulse voltage:	6 kV
Rated current (A):	16 A
Pollution degree:	3
Flammability:	UL94 V-0
Contact resistance:	< 5 mOhm
Number of contacts:	8
Termination methods:	Crimp termination
Material:	Polyamide, glass fibre-reinforced
Cycle of mechanical operation:	500
Certifications:	UL-tested: UL File Number: E75770
Temperature range:	-40°C to +125°C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

©2018 Lapp Group - Technical changes reserved

EPIC® MH 8

Article number	Article description	Contact type	Number of operating contacts	Slots
44423220	EPIC® MHS 8 CM	male	8	1
44423221	EPIC® MHB 8 CM	female	8	1

©2018 Lapp Group - Technical changes reserved