Specifications

Eaton EBF2330V1



Catalog Number: EBF2330V1

Eaton Bussmann series low voltage NH fuse base, Fuse rail, low voltage, 400 A, AC 690 V, NH1, NH2, 3P, IEC, 185 mm busbar, V-terminals with V-clamps

General specifications

Product Name
Eaton Bussmann series low voltage NH fuse base

Catalog Number
EBF2330V1

EAN
5027590336307

Product Length/Depth
675 mm

Product Height
162 mm

Product Width
103 mm

Product Weight
2940 g

Compliances
CE

Certifications
IEC 60269-1
IEC 60269-2

Powering Business Worldwide

Product specifications

Type

Fuse accessory

Application

Transformer substations, distribution boards, feeder pillars, cable distribution cabinets

Amperage Rating

400 A

Rated permanent current (Iu)

400 A

Conditioned rated short-circuit current Iq

0.1 kA

Double interrupting

No

Number of poles

Three-pole

Construction size (fuse inserts)

NH1, NH2

Distance

Between rail center: 185 mm

Electrical connection type of main circuit

Cable clamp

Construction size

NH1
NH2

Fuse shape

Vertical

Release indication

None

Suitable for

NH2

Suitable for fuses

NH2

Mounting method

Busbar

Voltage rating

690

Resources

Brochures

eaton-bussmann-series-ebf-vertical-fuse-rail-datasheet-10240en-us.pdf

Catalogs

CA134002EN

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

Declarations of conformity

UKCA Vertical NH fuse rails for NH fuse-links sizes 00 to 3

CE Vertical NH fuse rails for NH fuse-links sizes 00 to 3

Technical data sheets

10275 EBV Vertical fuse switch-disconnector

Technical service bulletins

10293 EBH Horizontal switch-disconnector

Electrical connection type

Cable clamp

Model

Fuse base

Rated operating voltage (Ue) at AC - max

690 V

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia