Specifications

Eaton 278636

Catalog Number: 278636

Eaton Moeller series xEffect - FAZ MCB. FAZ, 1-pole+N, tripping characteristic: B, rated current In: 2 A



General specifications

Product Name	**Catalog Number**
Eaton Moeller series xEffect - FAZ MCB	278636
EAN	**Product Length/Depth**
4015082786366	80 mm
Product Height	**Product Width**
75.5 mm	36 mm
Product Weight	**Compliances**
0.201 kg	RoHS conform

Certifications

EN45545-2

IEC 61373

Powering Business Worldwide

Product specifications

Used with

FAZ

Miniature circuit breaker

Type

FAZ

Miniature circuit breaker

Special features

Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity

Application

Switchgear for industrial and advanced commercial applications

xEffect - Switchgear for industrial and advanced commercial applications

Amperage Rating

2 A

Features

Additional equipment possible

Concurrently switching N-neutral

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Resources

Catalogs

eaton-xeffect-industrial-switchgear-range-catalog-ca003002en-en-us.pdf

Characteristic curve

eaton-xeffect-faz-mcb-characteristic-curve.jpg

Declarations of conformity

DA-DC-03_FAZ-B-C-D

Drawings

eaton-xeffect-faz-mcb-dimensions-002.jpg

eaton-xeffect-faz-mcb-3d-drawing-008.jpg

eaton-xeffect-faz-mcb-3d-drawing-007.jpg

eaton-xeffect-faz-mcb-3d-drawing.jpg

eCAD model

ETN.FAZ-B2_1N.edz

Installation instructions

IL019140ZU

mCAD model

eaton-faz_mcb_1pn_2p-3d-model.stp

eaton-faz_mcb_1pn_2p-drawing.dwg

PEP Eco-passport

EATO-00047-V01.01-EN

Wiring diagrams

eaton-xpole-mmc4-6-m-mcb-wiring-diagram.jpg

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Pollution degree

2

Degree of protection

IP20

Equipment heat dissipation, current-dependent

1.5 W

Rated impulse withstand voltage (Uimp)

4 kV

Breaking capacity

10 kA (UL1077)

Tripping characteristic

B

Ambient operating temperature - max

75 °C

Ambient operating temperature - min

-25 °C

Built-in depth

70.5 mm

Connectable conductor cross section (multi-wired) - max

25 mm²

Connectable conductor cross section (multi-wired) - min

1 mm²

Connectable conductor cross section (solid-core) - max

25 mm²

Connectable conductor cross section (solid-core) - min

1 mm²

Current limiting class

3

Frequency rating - max

60 Hz

Frequency rating - min

50 Hz

Heat dissipation capacity

0 W

Heat dissipation per pole, current-dependent

0 W

Voltage rating (IEC/EN 60898-1)

240 VAC

Width in number of modular spacings

2

Voltage type

AC

Overvoltage category

III

Number of poles

Single-pole + N

Release characteristic

B

Number of poles (protected)

1

Number of poles (total)

2

Operational voltage (IEC/EN 60947-2) - max

254 VAC

Rated insulation voltage (Ui)

440 V

Rated operational current for specified heat dissipation (In)

2 A

Rated operational voltage (Ue) - max

230 V

Rated service short-circuit breaking capacity (IEC/EN 60898-1)

7.5 kA

Rated service short-circuit breaking capacity (IEC/EN 60947-2)

7.5 kA

Rated short-circuit breaking capacity (EN 60898) at 230 V

10 kA

Rated short-circuit breaking capacity (EN 60898) at 400 V

10 kA

Rated short-circuit breaking capacity (IEC 60947-2) at 230 V

15 kA

Rated short-circuit breaking capacity (IEC 60947-2) at 400 V

15 kA

Rated switching capacity (IEC/EN 60898-1)

10 kA

Rated switching capacity (IEC/EN 60947-2)

15 kA

Rated switching capacity (IEC/EN 60947-2) at max voltage rating

10 kA

Static heat dissipation, non-current-dependent

0 W

Power loss

1.6 W

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia