# DATASHEET - XP2N4F-R-MCB06

**Partition; 2xNZM4 component mounting area/cable connection area; fixed mounting with remote operator; main busbar back; W=600mm**

**Part no.** **XP2N4F-R-MCB06**
**178613**

| General specifications | | | |
|---|---|---|---|
| Product name | | | Eaton xEnergy Main LV switchgear |
| Part no. | | | XP2N4F-R-MCB06 |
| EAN | | | 4015081739424 |
| Product Length/Depth | | | 261 millimetre |
| Product height | | | 60.5 millimetre |
| Product width | | | 510 millimetre |
| Product weight | | | 1.348 kilogram |
| Compliances | | | RoHS conform |
| Product Tradename | | | xEnergy Main |
| Product Type | | | LV switchgear |
| Product Sub Type | | | None |
| Public Consumption | | | Yes |
| PDH Status | | | Active |
| Product Family Description | | | ES-PMCC-PDC-Eaton xEnergy Main LV switchgear |
| Globally Marketable | | | Yes |

## Technical data ETIM 9.0

Cabinet enclosures (EG000011) / Divider panel (enclosure/cabinet) (EC002525)

Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Panel (electrical cabinet) / Divider panel (electrical cabinet) (ecl@ss13-27-18-21-02 [AKE424019])

| | | | |
|---|---|---|---|
| Modular spacing | | mm | 12.5 |
| Suitable for enclosure building width | | mm | 600 |
| Suitable for enclosure building depth | | mm | 0 |
| Width | | mm | 510 |
| Height | | mm | 60.5 |
| Material | | | Steel |
| Surface finishing | | | Galvanized |
| Colour | | | Stainless steel |
| RAL-number | | | 0 |
| With cable entry | | | Yes |
| Number of height units | | | 0 |
| With lock | | | Yes |
| Construction type | | | Individual part |
| For internal separation form 2a | | | No |
| For internal separation form 2b | | | No |
| For internal separation form 3a | | | No |
| For internal separation form 3b | | | No |
| For internal separation form 4a | | | No |
| For internal separation form 4b | | | Yes |


© 04/2023 by Eaton Industries GmbH