DATASHEET - S2-KLV

Socket outlet 2-position; with EURO2 adapter; with plug-in units; without input wiring

Part no. **S2-KLV**
178971

General specifications	
Product name	Eaton xComfort KLV schuko socket
Part no.	S2-KLV
EAN	4015081742882
Product Length/Depth	47 millimetre
Product height	102 millimetre
Product width	61 millimetre
Product weight	0.14 kilogram
Compliances	RoHS conform
Product Tradename	xComfort KLV
Product Type	Accessories
Product Sub Type	Schuko socket
Delivery program	
Type	Additional equipment for KLV multimedia distribution board
Model	Other Protective contact (SCHUKO)
Accessory/spare part type	KLV
Color	White
Nominal current	16 A
Number of phases	2
Technical Data - Electrical	
Nominal voltage - max	230 V
Fault current rating	1000 mA
Frequency rating - min	50 Hz
Frequency rating - max	50 Hz
Type of USB power supply	Other
Technical Data - Mechanical	
Surface finishing	Glossy
Surface protection	Other
Mounting method	Other
Material	Plastic
Material quality	Thermoplastic
Degree of protection (IP)	IP00
Number of active pins (flat)	0
Number of active pins (round)	2
Number of modules (module system)	2
Number of socket outlets (switchable)	0
Number of units	2
Connection type	Plug clamp
Fastening type	Mounting with screw
Impact strength	Other
Additional information	
Features	Halogen free Insulated mounting Protective contact
Fitted with:	Loop through function
Imprint/indication	None
RAL-number (Akin)	9010

Special power supply			Other
Used with			Socket outlet with EURO2 insert

Technical data ETIM 9.0

Domestic switching devices (EG000013) / Socket outlet (EC000125)			
Electric engineering, automation, process control engineering / Electrical installation, device / Installation switch set / Plug socket (ecl@ss13-27-14-40-42 [AKE352019])			
Model			Other
Concurrently switching neutral conductor			No
Protective contact			Other
Number of active contacts (round)			2
Number of active contacts (flat)			0
Number of active contacts (square)			2
With signal lamp			No
Number of ports USB-A			0
Number of ports USB-C			0
Max. current rating of USB power supply		A	0
Number of units			2
Number of modules (module system)			2
Number of socket outlets switchable			0
Number of phases			2
Imprint/indication			None
Connection type			Push-in clamp
With hinged lid			No
With enhanced contact protection			No
Label space/information surface			No
Colour			White
RAL-number (similar)			9010
Metallic colour			No
Transparent			No
Lockable			No
Eject-mechanism			No
Insulated mounting			Yes
With function lighting			No
With orientation lighting			No
Over voltage protection			No
Fault current protection			No
With miniature fuse			No
Special power supply			Other
Mounting method			Other
Type of fastening			Mounting with screw
Material			Plastic
Material quality			Thermoplastic
Halogen free			Yes
Surface protection			Other
Surface finishing			Glossy
Anti-bacterial treatment			No
With loop through function			Yes
Number of loop throughs			2
With on/off switch			No
Colour of switch operator			Other
Rotated central insert			No
Nominal current		A	16
Nominal voltage		V	230
Frequency		Hz	50 - 50
Rated fault current		mA	1000

Suitable for degree of protection (IP)			IP00
Impact strength			Other
Device width		mm	61
Device height		mm	102
Device depth		mm	47
Min. depth of built-in installation box		mm	36
Compatible with Apple HomeKit			No
Compatible with Amazon Alexa			No
Compatible with Google Assistant			No
IFTTT support available			No
With Wi-Fi signal repeater			No
With built-in bluetooth speaker			No
For heavy conditions according to VDE			No
Compliant with UK Building Regulations Part M			No

© 04/2023 by Eaton Industries GmbH