View product details on medias

26.12.2024, 06:13:53 UTC

SCHAEFFLER



FAG

6226-2Z-C3

Deep groove ball bearing

Deep groove ball bearing 62..-2Z, single row, shields, steel sheet metal cage

Technical information





Your current product variant

Sealing	2Z	Non-contact shield on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	GA13	Ball bearing and insert bearing grease, standard for D>62mm
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	130 mm	Bore diameter
D	230 mm	Outside diameter
B	40 mm	Width
C_r	177,000 N	Basic dynamic load rating, radial
C_{0r}	146,000 N	Basic static load rating, radial
C_{ur}	7,700 N	Fatigue load limit, radial
n_G	3,250 1/min	Limiting speed
$n_{\vartheta r}$	3,900 1/min	Reference speed
≈m	6.14 kg	Weight

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all further information and guidelines for this product.For further information you can use the contact form on our website

Mounting dimensions

$d_{a\ min}$	144 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	216 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	2.5 mm	Maximum fillet radius

Dimensions

r_{min}	3 mm	Minimum chamfer dimension
D_1	198.64 mm	Shoulder diameter outer ring
D_2	203.46 mm	Caliber diameter outer ring
d_1	161 mm	Shoulder diameter inner ring

Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Calculation factors

f_0	14.5	Calculation factor

Characteristics

- Radial load
- Axial load in one direction
- Axial load in two directions
- Lifetime lubrication, freedom from maintenance
- Grease Lubrication
- Sealed on both sides

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all further information and guidelines for this product.For further information you can use the contact form on our website