PILZ
THE SPIRIT OF SAFETY

PIT esb1.2 safe contact block 2 n/c 400301



PITestop, contact block, 1 N/C + 1 N/C with monitoring, terminals (screw type).

Technical details

General data	
Approval:	cULus Listed, EAC (Eurasian), TÜV
Self-monitored:	yes
Technical data	
Electrical data	
Min. contact current:	1 mA
Emergency stop	
Switch cap. E-STOP to standard:	EN 60947-5-1
Contact material E-STOP:	AgNi
Environmental data	
Ambient temperature:	-30 - 85 °C
Pollution degree clear.&creep.:	3
Mechanical data	
Connection terminal:	Screw terminal
Height dimension:	37 mm
Width dimension:	27 mm
Depth dimension:	43.6 mm
Net weight:	42 g
Gross weight:	45 g
Environment	

RoHS directive:	2011/65/EU
RoHS conformity:	yes
RoHS exceptions:	no
REACh compliance:	Contains no SVHC substances
WEEE classifikation (08/2018):	5 devices (feed size < 50cm)
Commercial data	
Harmonized System Code:	85365080
UNSPSC 25:	39122216
EAN-Code:	4046548003796
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27371302
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000017
ETIM Reference Feature:	EC000041
Volume:	0 dm3