*Date: 12/04/2023*

# PSD-4; 0...16 bar gauge ; two switching outputs (PNP/NPN)

## PSD-4; 0...16 bar gauge ; two switching outputs (PNP/NPN)

| | | |
|---|---|---|
| Item number: | 45824215 | |
| Quantity: | 1 pcs. | |
| Order code: | PSD-4-9Z-BG416-861Z-WW-ZZ | W1011PS4Z-SZAB-P-GSFI |
| Overview: | PSD-4; 0...16 bar gauge ; two switching outputs (PNP/NPN)<br>Electronic pressure switch with display<br>Output signal: two switching outputs (PNP/NPN)<br>IO-Link: without<br>Power supply: 15...35 V DC<br>Measuring range: 0...16 bar gauge<br>Process connection: G 1/2 B, flush diaphragm with O-ring<br>Sealing: NBR<br>Media temperature: -20 … 85 °C (-4 ... +185 °F)<br>El. connection: Circular connector M12x1 (4-pin)<br>pin assignment el. connection: U+=1, U-=3, SP1=4, SP2=2<br>Accuracy: ± 0.5% of span<br>Approvals: cULus<br>with test protocol<br>Specifications according to data sheet: PE 81.86 | |
| Details: | PSD-4; 0...16 bar gauge ; two switching outputs (PNP/NPN)<br>Electronic pressure switch with display<br>Output signal: two switching outputs (PNP/NPN)<br>IO-Link: without<br>Power supply: 15...35 V DC<br>Measuring range: 0...16 bar gauge<br>Process connection: G 1/2 B, flush diaphragm with O-ring<br>Sealing: NBR<br>Media temperature: -20 … 85 °C (-4 ... +185 °F)<br>El. connection: Circular connector M12x1 (4-pin)<br>pin assignment el. connection: U+=1, U-=3, SP1=4, SP2=2<br>Accuracy: ± 0.5% of span<br>Approvals: cULus<br>with test protocol<br>Specifications according to data sheet: PE 81.86 | |

*© 2023 - WIKA Instruments s.a.r.l.*