Matchcode	Description	Picture	Technical data	Colours
2 mm-Programme				
EPB 6053 Ni / ..(colour)	**Press-in socket** ▪ for pressing into panels up to 6 mm thick ▪ hole Ø 3.9 ▪ accesoires: mounting with press-in tool WKZ EPB2		terminal: PIN Ø 1.5 x 8 transition resistance: 7 mΩ rated voltage: 33 VAC / 70 VDC rated current: 10 A operating temperature: -40 °C … +90 °C	black, red, blue, yellow, green, grey, brown, white, purple
KURZ 5741 / 5.08-2 IG MB Ni / ..(colour) KURZ 5741 / 5.08-2 IG MB Au / ..(colour)	**Connecting plug** ▪ moulded insulation ▪ with rear socket Ø 2 mm		terminal: socket transition resistance: 5 mΩ (Ni) / 3 mΩ (Au) rated voltage: 33 VAC / 70 VDC rated current: 12 A operating temperature: -40 °C … +90 °C	black
2 mm-Safety-Programme				
SAK 6715 Ni / 2 / ..(colour)	**Safety crocodile clip** ▪ insulated ▪ socket Ø 2 mm ▪ contact: crocodile jaws ▪ grips up to Ø 8 mm		terminal: socket transition resistance: < 15 mΩ rated voltage: 600 V CAT II rated current: 10 A operating temperature: -25 °C … +80 °C	black, red, blue, yellow, green, white
4 mm-Programme				
EPB 6792 Ni / ..(colour)	**Press-in socket** ▪ for pressing into panels up to 6 mm thick ▪ hole Ø 6.8 ▪ accesoires: mounting with press-in tool WKZ EPB4		terminal:FR 4.8 x 0.8 transition resistance: 4 mΩ rated voltage: 33 VAC / 70 VDC rated current: 24 A operating temperature: -40 °C … +90 °C	black, red blue, yellow green, grey brown, white purple