KombiSIGN 70 / Flash Beacon 842

# Flashing light element 24VDC BU



| | |
|---|---|
| **Part No.:** | **842.510.55** |
| **Series:** | **KombiSIGN 70** |

| **MECHANICAL DATA** | |
|---|---|
| Height | 66 mm |
| Diameter | 70 mm |
| Materials | PC |
| Dome colour | Blue |
| Protection category | IP54 |
| Working temperature minimum | -20°C |
| Working temperature maximum | +50°C |
| Weight with packaging | 96 g |
| Product weight | 84 g |

| **ELECTRICAL DATA** | |
|---|---|
| Operating voltage | 24V |
| Operating voltage type | DC |
| Operating voltage tolerance | +/- 10% |
| Rated operational voltage | 24 VDC |
| Rated operational current | 80 mA |
| Rated inrush current | 250 mA |
| Protection class | Protection class 2 |
| Pollution degree | 3 |

| **OPTICAL DATA** | |
|---|---|
| Light source | Xenon |
| Light colour | Blue |
| Optical signal image | Flash |
| Flash frequency | 1 Hz |
| Flash output | 1 J |
| Service life optical | 4 million flashes minimum |

| **APPROVAL DATA** | |
|---|---|
| Conforms with CE | Yes |
| WEEE | Yes |
| Conforms with RED directive | No |
| Conforms with ATEX-directive | No |
| Conforms with CCC | No |
| Conforms with UL | cULus |
| UL Type Rating | Type 12 |
| Conforms with FCC | No |
| Conforms with IC | No |
| EAC certificate available | Yes |


! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

KombiSIGN 70 / Flash Beacon 842

# Flashing light element 24VDC BU

| | |
|---|---|
| Conforms with UKCA (Importer) | Yes (WERMA (UK) Ltd.) |
| Conforms with CMIM | No |
| Conforms with AS-I | No |
| ICAO Certification | No |
| Conforms with DNV | No |
| Conforms with RoHS CN | No |
| Conforms with VdS | No |

**DRAWING**




! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.