SELF-FASTENING NITRILE BUTADIENE RUBBER (NBR) HOSE

Email Print



Parker Legris self-fastening hose is designed according to CNOMO E07.21.115N*.
This range of hose should be used with Legris barb connectors and provides both the reliability of self-fastening technology and simplicity of installation.

PART NUMBER:
1040H56 02

TUBING MATERIAL:
NITRILE - TEXTILE

TUBE I.D. (MM):
6,3

TUBE O.D. (MM):
13

COLOR:
GREEN

DIAMETER NOMINAL (DN):
1/4

LENGTH (M):
40

Reset Attributes

WHERE TO BUY

PRODUCT OVERVIEW -

TECH SPECIFICATIONS +

Print Tech Specifications

PERFORMANCE CHARACTERISTICS

MAXIMUM PRESSURE (BARG)

16

MINIMUM WORKING TEMPERATURE (°C)

-20

MAXIMUM WORKING TEMPERATURE (C)

100

WEIGHT (KG/PACKAGE)

7

MAXIMUM BEND RADIUS (MM)

60

NUMBER OF TUBES

1

APPLICATION

In-Plant Automotive, Cooling, Welding Robots, Pneumatics, Industrial Machinery

MEDIA

Coolants, compressed air

CERTIFICATES

NFT 46-019-1, NFT 47 252, RG: 1907/2006 (REACH), DI: 2002/95/EC (RoHS), 2011/65/EC, CNOMO: E07.21.115N//*CAUTION: CNOMO certification is valid exclusively for red and green hose, only when connected to Legris' CNOMO-certified barb connectors 0132, 0133

Print Tech Specifications

PRODUCT SUPPORT +

RECOMMENDED



Adaptors, Plugs and Manifolds

CONTACT US

Parker Hannifin Manufacturing France SAS

Fluid System Connectors Division Europe
Parc Alcyone - Bat. D
1 rue André et Yvonne Meynier - CS 46911
35069 Rennes Cedex France

Phone
Phone: +33 (0) 2-99-25-55-00

EMAIL PARKER

Parker Hannifin +

Products
About Parker
Investors
Community
Careers

Global Operations +

Divisions
Sales Companies
Worldwide Locations
Distribution Network