Specifications

Eaton 271454

Catalog Number: 271454

Eaton Moeller series NZM - Molded Case Circuit Breaker. Rotary handle, black, lockable on the handle, NA type



General specifications

Product Name
Eaton Moeller series NZM operating element NA

Catalog Number
271454

EAN
4015082714543

Product Length/Depth
85 mm

Product Height
100 mm

Product Width
105 mm

Product Weight
0.33 kg

Compliances
IEC
UL/CSA
RoHS conform

Certifications
CSA (File No. 22086)
UL listed
CSA-C22.2 No. 5-09
CSA (Class No. 1437-01)
UL (File No. E140305)
CE marking
CSA certified
UL489
UL (Category Control Number DIHS)
IEC60947

Powering Business Worldwide

Product specifications

Used with

NZM2, N(S)2

Type

Accessory Rotary handle on switch with door interlock

Special features

Complete with rotary drive and insulating surround Cannot be combined with mechanical interlock Makes it possible to operate the switch with a rotational movement and provides locking facilities

Features

Lockable

Standard: black / gray

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Resources

Brochures

eaton-digital-nzm-brochure-br013003en-en-us.pdf

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Declarations of conformity

DA-DC-03_NZM2

Drawings

eaton-circuit-breaker-padlock-nzm-rotary-handle-dimensions.eps

eaton-circuit-breaker-rotary-handle-nzm-rotary-handle-dimensions-002.eps

eaton-circuit-breaker-nzm-rotary-handle-dimensions-006.eps

eaton-circuit-breaker-rotary-handle-nzm-rotary-handle-3d-drawing.eps

Installation instructions

eaton-door-coupling-rotary-handle-nzm1-2-xt-il01203005z.pdf

Installation videos

Introduction of the new digital circuit breaker NZM

The new digital NZM Range

mCAD model

DA-CS-nzm2_xd

DA-CD-nzm2_xd

Technical data sheets

eaton-nzm-technical-information-sheet

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Color

Black

Fitted with:

Padlock

Frame

NZM2

Suitable for

Switch disconnector

Power circuit breaker

Cover/door type

Door interlock not defeated in the locked OFF and ON positions

Door opens only with active rotation beyond the 0 position

Door interlock can be defeated from the outside using a 1 mm pin

Door interlock cannot be combined with mechanical locking

Door interlock in ON position

Door interlock can only be switched ON when the door is closed

Locking facility

Can also be modified in I position

Lockable on the 0 position on the handle using up to 3 padlocks

Also available with door interlock e.g. for MCC service distribution

Degree of protection / NEMA enclosure type

IP40

4X. 12

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia