PRODUCT-DETAILS

TF96-78

TF96-78 Thermal Overload Relay 65 ... 78 A



General Information

Extended Product Type	TF96-78
Product ID	1SAZ911201R1004
EAN	4013614483011
Catalog Description	TF96-78 Thermal Overload Relay 65 ... 78 A
Long Description	The TF96-78 thermal overload relay is an economic electromechanical protection device for the main circuit. It offers reliable and fast protection for motors in the event of overload or phase failure. The device has trip class 10. Further features are the temperature compensation, trip contact (NC), signal contact (NO), automatic- or manual reset selectable, trip-free mechanism, STOP function and a trip indication. The overload relays are connected directly to the block contactors. Single mounting kits are available as accessory.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	2CDC106069D0201

© 2024 ABB. All rights reserved.

Instructions and Manuals	2CDC106052M6803
Instructions and Manuals (Part 2)	1SAC200017M0002
Ex Operating Instructions	2CDC106086M6801
Time-Current Characteristic Curve	1SAZ900502F0004
CAD Dimensional Drawing	2CDC001079B0201
Dimension Diagram	1SAZ900401F0001

Dimensions

Product Net Width	69.9 mm
Product Net Height	106.9 mm
Product Net Depth / Length	106.3 mm
Product Net Weight	0.52 kg

Technical

Setting Range	65 ... 78 A
Rated Operational Voltage	Auxiliary Circuit 600 V AC/DC Main Circuit 690 V AC Main Circuit 440 V DC
Rated Operational Current (I_e)	78 A
Rated Frequency (f)	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC Main Circuit 50 Hz Main Circuit 60 Hz
Rated Impulse Withstand Voltage (U_{imp})	Auxiliary Circuit 6 kV Main Circuit 8 kV
Rated Insulation Voltage (U_i)	690 V
Number of Poles	3
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Number of Protected Poles	3
Conventional Free-air Thermal Current (I_{th})	Auxiliary Circuit NC 6 A Auxiliary Circuit NO 4 A
Rated Operational Current AC-15 (I_e)	(120 V) NC 3 A (120 V) NO 0.5 A (240 V) NC 3 A (240 V) NO 0.5 A (400 V) NC 0.75 A (400 V) NO 0.5 A (500 V) NC 0.75 A (500 V) NO 0.5 A
Rated Operational Current DC-13 (I_e)	(125 V) NC 0.55 A (125 V) NO 0.55 A (24 V) NC 1.25 A (24 V) NO 1.25 A (250 V) NC 0.27 A (250 V) NO 0.27 A (500 V) NC 0.15 A (500 V) NO 0.15 A (60 V) NC 0.55 A (60 V) NO 0.55 A
Degree of Protection	Housing IP20 Main Circuit Terminals IP10
Pollution Degree	3
Connecting Capacity	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm²

© 2024 ABB. All rights reserved.

Auxiliary Circuit	Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm² Flexible 1/2x 0.75 ... 1 mm² Flexible 1/2x 1 ... 2.5 mm² Rigid 1/2x 0.75 ... 4 mm²
Connecting Capacity Main Circuit	Flexible with Ferrule 1/2x 6 ... 35 mm² Flexible with Ferrule 1x 6 ... 50 mm² Flexible with Insulated Ferrule 1/2x 6 ... 16 mm² Flexible with Insulated Ferrule 1x 6 ... 50 mm² Flexible 1/2x 6 ... 35 mm² Flexible 1x 6 ... 50 mm² Rigid 1/2x 6 ... 35 mm² Rigid 1x 6 ... 50 mm²
Tightening Torque	Auxiliary Circuit 1 ... 1.2 N·m Main Circuit 6.0 ... 9.0 N·m
Wire Stripping Length	Auxiliary Circuit 9 mm Main Circuit 20 mm
Recommended Screw Driver	Auxiliary Circuit Pozidriv 2 Main Circuit Hexagon 4
Mounting Position	1 ... 6
Power Loss	at Rated Operating Conditions per Pole 2.7 ... 3.8 W
Suitable For	AF80 AF96
Standards	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1 IEC 60335-2-40 A2L

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V AC
Contact Rating UL/CSA	(NC:) B600 (NC:) Q600 (NO:) Q600 (NO:) D300
Connecting Capacity Main Circuit UL/CSA	Flexible 1x 8-1 AWG Flexible 2x 8-3 AWG Stranded 1x 8-1 AWG Stranded 2x 8-3 AWG
Connecting Capacity Auxiliary Circuit UL/CSA	Flexible 1/2x 18-12 AWG Stranded 1/2x 18-12 AWG
Tightening Torque UL/CSA	Auxiliary Circuit 9 ... 11 in·lb Main Circuit 53 ... 80 in·lb

Environmental

Ambient Air Temperature	Operation -40 ... +70 °C Operation Compensated -40 ... +70 °C Storage -50 ... +80 °C
Ambient Air Temperature Compensation	Yes
Maximum Operating Altitude Permissible	2000 m
Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 25g
Resistance to Vibrations	5g 3 ... 150 Hz
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525

Material Compliance

Conflict Minerals Reporting Template	9AKK108467A5658

© 2024 ABB. All rights reserved.

(CMRT)	
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Circular Value

End of Life Instructions	1SAC200334H0001

Eco Transparency

Environmental Product Declaration - EPD	1SAC200249H0001
Environmental Information	1SAC200059H0009

Certificates and Declarations

A2L Certificate - IEC	1SAA941000-4601
ABS Certificate	1SAA941003-0101
ATEX Certificate	1SAA941006-3901
BV Certificate	1SAA941001-0203
CB Certificate	1SAA941015-2001
CQC Certificate	CQC2014010309689434
Declaration of Conformity - CCC	2020980309000292
Declaration of Conformity - CE	1SAD101100-3503
Declaration of Conformity - UKCA	1SAD201100-3503
DNV GL Certificate	1SAA941004-0301
EAC Certificate	1SAA941002-2701
IECEx Certificate	1SAA941002-4001
LR Certificate	1SAA941003-0501
RINA Certificate	RINA_ELE098115XG
RMRS Certificate	1SAA941002-0701
UL Certificate	E48139-20130329

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	97 mm
Package Level 1 Height	121 mm
Package Level 1 Depth / Length	97 mm
Package Level 1 Gross Weight	0.62 kg
Package Level 1 EAN	4013614483011
Package Level 2 Units	12 piece
Package Level 2 Width	280 mm
Package Level 2 Height	210 mm
Package Level 2 Depth / Length	395 mm
Package Level 2 Gross Weight	7.826 kg

© 2024 ABB. All rights reserved.

Package Level 2 EAN	4013614485459

Classifications

Object Classification Code	F
ETIM 4	EC000106 - Thermal overload relay
ETIM 5	EC000106 - Thermal overload relay
ETIM 6	EC000106 - Thermal overload relay
ETIM 7	EC000106 - Thermal overload relay
ETIM 8	EC000106 - Thermal overload relay
eClass	V11.0 : 27371501
UNSPSC	39122330
IDEA Granular Category Code (IGCC)	5366 >> Thermal overload relay
E-Number (Finland)	3706593
E-Number (Norway)	4116797
E-Number (Sweden)	3210273

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
1SAZ901901R1001	DB96 Single Mounting Kit	DB96	1	piece
1SAX101911R1001	DRS-F-01 Remote Reset Coil	DRS-F-01	1	piece
1SAX101911R1002	DRS-F-02 Remote Reset Coil	DRS-F-02	1	piece
1SAX101911R1003	DRS-F-03 Remote Reset Coil	DRS-F-03	1	piece
1SAX101911R1004	DRS-F-04 Remote Reset Coil	DRS-F-04	1	piece
1SAZ701904R1001	DRS-F-TF-01 Remote Coil	DRS-F-TF-01	1	piece
1SAZ701904R1002	DRS-F-TF-02 Remote Coil	DRS-F-TF-02	1	piece
1SAZ701904R1003	DRS-F-TF-03 Remote Coil	DRS-F-TF-03	1	piece
1SAZ701904R1004	DRS-F-TF-04 Remote Coil	DRS-F-TF-04	1	piece
1SAZ701903R1001	WRH-F Holder	WRH-F	1	piece
1SAZ701903R1011	WRB-400 Bowden Wire	WRB-400	1	piece
1SAZ701903R1012	WRB-600 Bowden Wire	WRB-600	1	piece
1SAZ701903R1013	WRB-1000 Bowden Wire	WRB-1000	1	piece
1SAZ701903R1030	WRBG Gasket	WRBG	1	piece
1SFA616162R1014	KPR3-101L Reset push button	KPR-101L	1	piece

Categories

Low Voltage Products and Systems → Control Products → Contactors → Thermal Overload Relays

© 2024 ABB. All rights reserved.



© 2024 ABB. All rights reserved.