SHT 6.3x32

Cartridge Fuse, 6.3x32 mm, 500 VAC, 1-8 A, High Breaking Capacity of 1500 A

new



UL 248-14 · 500 VAC · Time-Lag T

Description
- High breaking capacity
- High rated current
- Pigtails optional

Standards
- UL 248-14
- CSA C22.2 no. 248.14

Approvals
- UL File Number: E41599

Applications
- 3-phase applications
- Industrial electronic
- Photovoltaic
- Frequency converter
- Power electronics

References
Packaging Details
Pigtail Type SHT 6.3x32 Pigtail


Weblinks
pdf-datasheet, html-datasheet, General Product Information, Approvals, CE declaration of conformity, RoHS, CHINA-RoHS, REACH, e-Shop, SCHURTER-Stock-Check, Distributor-Stock-Check, Detailed request for product

Technical Data

Rated Voltage	500 VAC
Rated current	1 - 8 A
Breaking Capacity	1500 A
Characteristic	Time-Lag T
Mounting	Fuseholder / Clip
Admissible Ambient Air Temp.	-40 °C to 85 °C
Climatic Category	40/085/21 acc. to IEC 60068-1
Material: Tube	Ceramic
Material: Endcaps	Nickel-Plated Copper Alloy
Material: Axial Leads	Tin-Plated Copper
Unit Weight	2.84 g
Storage Conditions	0 °C to 60 °C, max. 70% r.h.
Product Marking	⊟, Type, Rated current, Rated voltage, Characteristic, Breaking capacity, Approvals

Dimension


6.3 mm



Pre-Arcing Time

Rated Current In	1.5 x In min.	2.1 x In max.	2.75 x In min.	2.75 x In max.	4.0 x In min.	4.0 x In max.	10.0 x In min.	10.0 x In max.
1 A - 1.6 A	60 min	30 min	400 ms	80 s	95 ms	5 s	10 ms	300 ms
2 A - 8 A	60 min	30 min	400 ms	80 s	150 ms	5 s	20 ms	300 ms

Time-Current-Curves



All Variants

Rated Current [A]	Rated Voltage [VAC]	Breaking Capacity	Voltage Drop 1.0 In max. [mV]	Power Dissipation 1.5 I_n max. [mW]	Melting I^2t 10.0 Intyp. [A^2s]	cULus	Order Number
1	500	1)	350	900	1.55	●	8020.5011
1	500	1)	350	900	1.55	●	8020.5011.G
1.25	500	1)	300	1000	3.15	●	8020.5012
1.25	500	1)	300	1000	3.15	●	8020.5012.G
1.6	500	1)	200	1100	5.4	●	8020.5013
1.6	500	1)	200	1100	5.4	●	8020.5013.G
2	500	1)	180	1200	10.5	●	8020.5014
2	500	1)	180	1200	10.5	●	8020.5014.G
2.5	500	1)	160	1300	20	●	8020.5015
2.5	500	1)	160	1300	20	●	8020.5015.G
3.15	500	1)	150	1400	39	●	8020.5016
3.15	500	1)	150	1400	39	●	8020.5016.G
4	500	1)	140	1500	71.4	●	8020.5017
4	500	1)	140	1500	71.4	●	8020.5017.G
5	500	1)	135	2200	84	●	8020.5018
5	500	1)	135	2200	84	●	8020.5018.G
6.3	500	1)	110	2200	225	●	8020.5019
6.3	500	1)	110	2200	225	●	8020.5019.G
8	500	1)	110	2600	390	●	8020.5020
8	500	1)	110	2600	390	●	8020.5020.G

Most Popular.

Rated Current [A]	Rated Voltage [VAC]	Breaking Capacity	Voltage Drop 1.0 In max. [mV]	Power Dissipation 1.5 I_n max. [mW]	Melting I^2t 10.0 Intyp. [A^2s]	Order Number

Availability for all products can be searched real-time:http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

1) 1500 A @ 500 VAC

Packaging Unit	xxxx.xxxx	Small Box Pack (10 pcs.)
	xxxx.xxxx.G	Bulk (1000 pcs.)

16.09.2014

The specifications, descriptions and illustrations indicated in this document are based on current information. All content is subject to modifications and amendments. Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability and test each product selected for their own applications.