Specifications

Eaton 121993



Catalog Number: 121993

Eaton Distribution parts. Phase busbar, 2-phase, 25qmm, pin, 1m, 3M/39

General specifications

Product Name	**Catalog Number**
Eaton Distribution parts	121993
EAN	**Product Length/Depth**
4015081201938	690 mm
Product Height	**Product Width**
37 mm	22 mm
Product Weight	**Compliances**
0.704 kg	RoHS conform

Powering Business Worldwide

Product specifications

Used with

BB-UL

Busbar

Type

BB-UL

Busbar

Features

Insulated

Can be cut to size

Accessory/spare part type

Busbar for miniature circuit breaker

Electric connection type

Pin

Rated operational current for specified heat dissipation (In)

100 A

Rated surge voltage

10 KV

Rated uninterrupted current (Iu)

100 A

Static heat dissipation, non-current-dependent

0 W

Suitable for number of devices

2

Application

Switchgear for industrial and advanced commercial applications

Number of poles

Thirty-nine-pole

Color

Other

Rated short-time withstand current (Icw)

0 kA

Ambient operating temperature - max

100 °C

Ambient operating temperature - min

-5 °C

Resources

Installation instructions

MA150501419

System overview

eaton-explosion-drawing-140311.eps

Cross section

25 mm²

Heat dissipation capacity

0 W

Heat dissipation per pole, current-dependent

0 W

Number of modular spacings

39

Number of phases

2

Pitch dimensions

0 mm

Rated operational voltage (Ue) - max

277 V

Rated conditional short-circuit current (Iq)

10 kA

Functions

Busbar

Suitable for

39 devices

Powering Business Worldwide

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia