Date: 11/04/2023

TR75 Resistance Themometer DiwiTherm®, with

TR75 Resistance Themometer DiwiTherm®, with

Item number: 48774184

Quantity: 1 pcs.

Order code: TR75-1-ZZZ-M-F-C-ZBK-ZZZ-R00300-DR-00300-Z-1Z ZZZ00000300AN
CERT22-EG32-AA-CA- - - - - - - - - - TE-CT3

Overview:
TR75 Resistance Themometer DiwiTherm®, with
digital Display
Specifications according to data sheet: TE 60.75
Power supply: Battery powered
Unit of measure: Metric (mm)
Temperature range: -40...+199,9 °C
Instrument version: Axial, panel mounting
Fitting style: Compression fitting with stainless steel ferrule
Thread size: 1/2 NPT
Lead wire insulation: Silicon jacket, shielded, application range -40...+180 °C
W-Dimension: 300 mm
Sensor diameter: 6.0 mm
Sheath material: Stainless steel 316 Ti (1.4571)
A-Dimension: 300 mm
Test certificate acc. to EN 10204 2.2
Certificate Language: English and German
Electrical Thermometer
Formal certificate: Manufactured according to state-of-the-art
Accuracy certificate: Certification of class and accuracy

Details:
TR75 Resistance Themometer DiwiTherm®, with
digital Display
Specifications according to data sheet: TE 60.75
Power supply: Battery powered
Unit of measure: Metric (mm)
Temperature range: -40...+199,9 °C
Instrument version: Axial, panel mounting
Fitting style: Compression fitting with stainless steel ferrule
Thread size: 1/2 NPT
Lead wire insulation: Silicon jacket, shielded, application range -40...+180 °C
W-Dimension: 300 mm
Sensor diameter: 6.0 mm
Sheath material: Stainless steel 316 Ti (1.4571)
A-Dimension: 300 mm
Test certificate acc. to EN 10204 2.2
Certificate Language: English and German
Electrical Thermometer
Formal certificate: Manufactured according to state-of-the-art

© 2023 - WIKA Instruments s.a.r.l.

Date: 11/04/2023

Accuracy certificate: Certification of class and accuracy

© 2023 - WIKA Instruments s.a.r.l.