# DATASHEET - P3-63/I3/SVB-SW

**On-Off switch, P3, 63 A, surface mounting, 3 pole, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position**

**Part no.** P3-63/I3/SVB-SW
**Catalog No.** 207336

## Delivery program

| | | | |
|---|---|---|---|
| Product range | | | On-Off switch |
| Part group reference | | | P3 |
| Stop Function | | | STOP function |
| | | | With black rotary handle and locking ring |
| Information about equipment supplied | | | Auxiliary contact or neutral conductor fitted by user. |
| Number of poles | | | 3 pole |
| **Auxiliary contacts** | | | |
| | | N/O | 0 |
|  | | N/C | 0 |
| Locking facility | | | Lockable in the 0 (Off) position |
| Degree of Protection | | | IP65 |
| Design | | | surface mounting |
| **Motor rating AC-23A, 50 - 60 Hz** | | | |
| 400 V | P | kW | 30 |
| Rated uninterrupted current | $I_u$ | A | 63 |
| Note on rated uninterrupted current $!_u$ | | | Rated uninterrupted current $I_u$ is specified for max. cross-section. |

## Technical data

### Contacts

| | | | |
|---|---|---|---|
| Mechanical variables | | | |
| Number of poles | | | 3 pole |
| Auxiliary contacts | | | |
| | | N/O | 0 |
| | | N/C | 0 |
| Electrical characteristics | | | |
| Rated uninterrupted current | $I_u$ | A | 63 |
| Note on rated uninterrupted current $!_u$ | | | Rated uninterrupted current $I_u$ is specified for max. cross-section. |
| Rated conditional short-circuit current | Iq | kA | 4 (Load side)<br>100 (Supply side) |


© 07/2022 by Eaton Industries GmbH