# 700-322-1BH01




## Output module digital for 300
### 16x

- 16 Outputs 24V DC

## Info

Digital output modules for the 300 series

The module has 16 outputs.

## Technical data

| | |
|---|---|
| **General information** | |
| Order number | 700-322-1BH01 |
| Article name | DEA 300, DC 24 V, 0.5 A, 16 outputs |
| Scope of delivery | DEA 300, DC 24 V, 0.5 A, 16 outputs |
| Dimensions (DxWxH) | 116 x 40 x 125 mm |
| Weight | Approx. 220g |
| Number of outputs | 16 |
| Power dissipation (nominal operation) | typ. 5 W |
| Front connectors | 20-pin |
| **Electrical isolation** | |
| from the backplane bus | Yes (optocoupler) |
| in groups to | 8 |
| **Supply voltage UP, US** | |
| Rated value | 0.5 A |
| Ripple USS | max. 3.6 V |
| Permissible range (with ripple) | +20 ... +30 V |
| Voltage for t < 10 ms | max. 50 V |
| Short-circuit protection | Electronic |
| Inductive cutoff voltage limit | -48 V |
| **Cable length** | |
| Unshielded | max. 600 m |
| Shielded | max. 1000 m |
| **Current draw** | |
| Internal (backplane bus) | Max. 100 m |
| External (from +24 V/L+) | typ. 120 mA |
| **Ambient conditions** | |
| Ambient temperature | 0 °C ... +60 °C |
| Transport and storage temperature | -25 °C ... +75 °C |
| Pullution degree | 2 |
| Protection rating | IP20 |
| Approvals | CE |