SITESAFE® HEARING DEFENDERS

With flexible reinforced plastic headbands, ABS cups and PVC cushions.

Model No.	Colour	Duty	Order Code
SSED29	Yellow	General	**SSF-958-4040K**

CE 2797
Approved
EN352-1: 2002
Complies With European Directive 2016/425

Requirements: This hearing protector complies with the requirements of the European Directive 2016/425 annex II by means of the European Standard EN352-1:2002 "Hearing protectors – general requirements – Part 1:Ear muff ".

Mark: The appropriate marking can be found on the cups.
CE mark was issued by the notified body: 2797
These hearing defenders satisfy the requirements in the small, normal and large size ranges **(EN 352-1 : 2002.)**

INSTRUCTIONS FOR USE

1. Open hearing defenders to maximum width and place both cups over ears. Always wear with headband over the head.
2. Position hearing defenders so that the cups completely enclose the ears and with the headband touching the head.
3. Adjust the pressure of the fit so that a good noise "seal" is achieved.

IT IS RECOMMENDED THAT THE WEARER SHOULD ENSURE THAT:

1. The hearing defenders are fitted, adjusted and maintained according with these instructions.
2. The hearing defenders are worn at all times in noisy surroundings.
3. The hearing defenders are regularly inspected for serviceability. If these recommendations are not adhered to, the protection afforded by the hearing defenders will be severely impaired.

HEADBAND ADJUSTMENT ABOVE THE HEAD USE:

1. Extend headband to maximum "open" position and place the cups over the ears with the headband passing over the head.
2. Settle the headband in position on the head while adjusting the height of the ear cups until they feel comfortable and the headband rests on top of the head to support the muffs.
3. The ear cushions should be a snug fit against the head.
4. Adjust the headband & ear cups to ensure an effective noise seal.

CARE AND CLEANING

Sponge clean with soapy water. Rinse thoroughly. Do not use alcohols or solvents. Foam liner should be allowed to air dry before re-inserting into the earcups. It is recommended that a disinfectant cleaner is used every 3 months.

STORAGE RECOMMENDATIONS

Hearing defenders should be stored in a plastic bag in a dry place, kept away from direct sunlight and not subjected to temperature conditions of below -20°c or above +40°c. Store away from any possible contaminants. Replace ear-muffs after 2 to 3 years normal use or sooner if they show any signs of deterioration.This product may be dversely affected by certain chemical substances. Further information should be sought from the manufacturer.

WARNING

Hearing defenders and in particular cushions may deteriorate, harden or deform with use and should be inspected at frequent intervals for cracking and leakage, for example. If any of these conditions become evident, the defender should be replaced. The fitting of hygiene covers to the cushions may affect the acoustic performance of earmuffs. User should permanently wear the headband earmuff in noisy environment.

Weight of the ear-muff : 157g

ATTENUATION DATA

Model SSED29 (SSF-958-4040K)

Test Frequency, Hz	63	125	250	500	1000	2000	4000	8000
Mean Attenuation, dB	18.1	15.0	18.3	26.8	37.5	29.5	35.8	36.1
Standard Deviation, dB	4.1	2.7	3.3	2.0	4.1	2.9	3.3	5.8
Assumed Protection Value dB	14	12.3	15.0	24.8	33.4	26.6	32.5	30.3

Attenuation Values: H = 29.2dB, M = 25.4dB, L = 17.9dB, SNR = 27.6dB in accordance with ISO/DIS 4869-2 (a =1)

Authorized Representative Manufacturer: Cromwell Tools Ltd.
CE, Cromwell Tools, P.O. Box 14, Wigston, Leicester, England LE18 1AT
LONG DAR PLASTIC CO., LTD.
No.140, Wu Gong Rd., New Taipei Industrial Park, Wu Gu Dist., New Taipei City 248, Taiwan (R.O.C.)

CE Approved BSI Group The Netherlands B.V., Registered In The Netherlands Under Number 33264284, At John M. Keynespein 9, 1066 Ep Amsterdam, The Netherlands A Member Of BSI Group Of Companies.

SITESAFE
P.O. Box 14, Wigston, Leicester, England LE18 1AT.
Sitesafe is a registered trade mark of The Kennedy Group Ltd.