TUFFSAFE
PROTECTION AT WORK

TUFFLITE NYLON LINED PU COATED GLOVES

EN420: 2003+A1:2009
Dexterity level: 5
PH level: Between 3.5 and 9.5

EN388:2016

4141X

Data Sheet

PU coated gloves provide great dexterity for handling goods that are dry or slightly damp with no or low cut risk



Liner: 13 gauge, 280g/m² nylon liner (black, grey or white)

Coating: Black, grey or white PU palm coating

Cuff: 13 gauge, 400g/m² nylon/elastic (black, grey or white) cuff with polyester colour coded binding for size identification

Mechanical Data

Abrasion resistance	Level 4
Blade cut resistance	Level 1
Tear resistance	Level 4
Puncture resistance	Level 1

Order Code	Colour	Size	Minimum Length (mm)
TFF-961-6407J	White	6	220
TFF-961-6408K	White	7	230
TFF-961-6409L	White	8	240
TFF-961-6410M	White	9	250
TFF-961-6411N	White	10	260

Order Code	Colour	Size	Minimum Length (mm)
TFF-961-6415R	Grey	6	220
TFF-961-6416S	Grey	7	230
TFF-961-6417T	Grey	8	240
TFF-961-6418V	Grey	9	250
TFF-961-6419W	Grey	10	260
TFF-961-6420X	Grey	11	270
TFF-961-6425A	Black	6	220
TFF-961-6426B	Black	7	230
TFF-961-6427C	Black	8	240
TFF-961-6428D	Black	9	250
TFF-961-6429E	Black	10	260

TUFFSAFE, Wigston, Leicester, England, LE18 2FS.
Tuffsafe is a registered trade mark of The Kennedy Group Ltd.

© Copyright 2017 - The Kennedy Group Ltd.