

SHORT IMPACT SOCKET (6PT.)

Suitable for working at narrow place

Real size



Standard Socket
4NV-24



Short Socket
4NV-24SS

Across flat size (mm)	Length (mm)		
	4NV-○○	4NV-○○SS	Difference
10	38	23.5	14.5
12	38	25	13
13	38	25	13
14	38	25.5	12.5
17	38	25.5	12.5
19	40	26.5	13.5
21	40	27.5	12.5
22	40	29.5	10.5
24	42	31.5	10.5

SHORT IMPACT SOCKET SET (with SOCKET HOLDER)

Models **HNV409SS**

Contents **9 Items**

- SH2410 with a socket holder (10 items type)
- Package size : w322 × d93 × h35mm
- Weight : 0.71kg • Qty./Carton : 1



sq.dr
12.7
mm
1/2"

NEW

6




HNV409SS

※ Socket holder is available for separate purchase. Please see P202.

SHORT IMPACT SOCKET (6PT.)

Models	Across Flat (mm)	Dimensions (mm)				Qty./ Carton (Generally)	Weight (g)
	S	D ₁	D ₂	L ₁	L		
4NV-10SS	10	16	25	5	23.5	10	43.0
4NV-12SS	12	19.5	25	6.5	25	10	47.5
4NV-13SS	13	21	25	6.5	25	10	49.0
4NV-14SS	14	22	25	7	25.5	10	51.0
4NV-17SS	17	26	26	7	25.5	10	59.0
4NV-19SS	19	29	28	8	26.5	10	76.0
4NV-21SS	21	31	28	9	27.5	10	81.5
4NV-22SS	22	32	28	11	29.5	10	88.0
4NV-24SS	24	35	28	13	31.5	10	103.0


※ This product is patent registered.



4NV-17SS



4NV-21SS



Most suitable when exchanging tractor tiller blade!

Pin/O-ring compatible chart

Models	4NV-	10SS ~ 24SS
Pin		P3020S
O-ring		RP20S

※ Within a plastic bag (10 pcs./pkg.)

※ This product is patent registered.

TONE Impact wrench.
AI4200 An installation example.



Product video

Combination of short type and angle type of impact wrench comes with tremendous power!

AIR IMPACT WRENCH, SHORT TYPE

Models **AI4200, AI4201**

sq.dr
12.7
mm
1/2"

Turn to P477 - 478 for more information.



AI4200

AI4201

AIR IMPACT WRENCH, SHORT TYPE

Models **AIA4140**

sq.dr
12.7
mm
1/2"

Turn to P479 for more information.



AIA4140



For impact wrenches

WARNING

- Use right size o-ring and pin securely fixed.
- O-ring and pin are consumptive parts. Replace those which are deteriorated or worn.