

SOCKET WRENCH

For impact
12.7

Available for impact socket with pin/O-ring inserted.
Better durability than resin tray.
Stable and easy arrangement with fixed clip.



STAINLESS TOOL
TITANIUM TOOL

TOOL SET

TOOL CASE

SOCKET
WRENCH

HEXAGON
WRENCH

T-TYPE
WRENCH

SPANNER
OFFSET WRENCH

SCREWDRIVER

BIT

ADJUSTABLE
WRENCH
PLIERS

SPECIALIZED
CAR EQUIPMENT

CYCLE TOOL

LED LIGHT

OTHER HAND
TOOLS

TORQUE
WRENCH

AIR TOOL



NV4132



CAUTION

- Beware at all time not to pinch hand / fingers.

Impact socket set with socket holder.



HNV406S

Electroless nickel plating.
Better appearance and anti-rust.



4NV-08




4NV-32

6-Point Strong Drive



- This product is patent registered.
- In case of out-of-stock, the impact socket will be automatically changed to double-grooved type.



Pin/O-ring compatible chart

Models	4NV-	08 ~ 36
Pin		P3020S
O-ring		RP20S

※ Within a plastic bag (10 pcs./pkg.)

IMPACT SOCKET SET (6pt.)

Models **NV4132**

Contents **15 Items**

Descriptions	Models/Specifications
IMPACT SOCKET	4NV- 10, 12, 13, 14, 17, 19, 21, 22, 24, 26, 27, 30, 32
IMPACT EXTENSION BAR	NE40-150
IMPACT BALL JOINT	NJ40

- Tool case : MCT2
- 6-Point Strong Drive
- Package size : w406 x d120 x h60mm
- Weight : 3.65kg Qty./Carton : 6



※ In case of out-of-stock, the impact socket will be automatically changed to double-grooved type.

IMPACT SOCKET SET (6pt.), with SOCKET HOLDER

Models **HNV406S**

Contents **6 Items**

Descriptions	Models
IMPACT SOCKET	4NV- 13, 14, 17, 19, 21, 24

- 6-Point Strong Drive
- SH2406 with a socket holder (6 items type)
- Package size : w322 x d93 x h35mm
- Weight : 0.68kg Qty./Carton : 1



※ This product is patent registered.

※ In case of out-of-stock, the impact socket will be automatically changed to double-grooved type.

IMPACT SOCKET (6pt.)

Models	Across Flat (mm)	Dimensions (mm)					Qty./Carton		Weight (g)
	S	D ₁	D ₂	L ₁	L	d	(Generally) (Store Center)		
4NV-08	8	14.0	25	6	38	7	10	6	64
4NV-09	9	15.0	25	8	38	7	10	6	66
4NV-10	10	16.0	25	9	38	8	10	6	67
4NV-11	11	17.5	25	10	38	9	10	6	71
4NV-12	12	19.5	25	11	38	10	10	6	76
4NV-13	13	21.0	25	11	38	10	10	6	82
4NV-14	14	22.0	25	12	38	11	10	6	83
4NV-15	15	23.0	25	12	38	11	10	6	86
4NV-16	16	24.0	25	12	38	14	10	6	85
4NV-17	17	26.0	26	13	38	14	10	6	100
4NV-18	18	27.0	26	13	40	15	10	6	103
4NV-19	19	29.0	28	14	40	16	10	6	112
4NV-20	20	30.0	28	15	40	16	10	6	116
4NV-21	21	31.0	28	15	40	20	10	6	115
4NV-22	22	32.0	28	15	40	21	10	6	119
4NV-23	23	33.0	28	15	40	20	10	6	122
4NV-24	24	35.0	28	16	42	20	10	6	134
4NV-25	25	37.0	30	18	44	22	10	6	151
4NV-26	26	38.0	30	18	44	22	10	6	156
4NV-27	27	39.0	30	18	44	22	10	6	160
4NV-28	28	40.0	30	18	45	22	10	6	172
4NV-29	29	41.0	30	20	45	22	10	6	171
4NV-30	30	42.0	30	20	46	25	10	6	176
4NV-32	32	45.0	30	20	46	25	10	6	201
4NV-33	33	46.0	30	22	48	25	10	6	207
4NV-34	34	47.0	30	22	48	25	10	6	217
4NV-35	35	48.5	30	22	48	25	10	6	225
4NV-36	36	50.0	30	22	51	30	10	6	258



- Use right size o-ring and pin securely fixed.
- O-ring and pin are consumptive parts. Replace those which are deteriorated or worn.