


LONG IMPACT SOCKET (6pt.)

Models	Invitation Dimensions (mm)	Dimensions (mm)						Qty./Carton		Weight (g)
		S	D ₁	D ₂	L ₁	L	d	(Generally)	(Store Center)	
4NV-12L150	12	18.0	25	20	150	10	5	5	6	270
4NV-13L150	13	19.0	25	20	150	10	5	5	6	317
4NV-14L150	14	20.0	25	20	150	11	5	5	6	334
4NV-17L150	17	24.5	26	24	150	14	5	5	6	426
4NV-19L150	19	27.0	28	24	150	16	5	5	6	509
4NV-21L150	21	28.5	28	24	150	18	5	5	6	522
4NV-22L150	22	30.5	28	25	150	18	5	5	6	569
4NV-24L150	24	33.5	28	25	150	20	5	5	6	683

6-Point Strong Drive

- ※ This product is patent registered.
- ※ In case of out-of-stock, the impact socket will be automatically changed to double-grooved type.



4NV-12L150



4NV-24L150

Pin/O-ring compatible chart

Models	4NV-	12L150 ~ 24L150
Pin		P3020S
O-ring		RP20S

※ Within a plastic bag (10 pcs./pkg.)

SOCKET HOLDER (ALUMINIUM TYPE)

Models SH2404, SH2406, SH2410, SH2412



Turn to P202 for more information.

SH2404



SH2406



SH2410



SH2412



For impact wrenches

WARNING

- Use right size o-ring and pin securely fixed.
- O-ring and pin are consumptive parts. Replace those which are deteriorated or worn.

For impact

12.7

STAINLESS TOOL
TITANIUM TOOL

TOOL SET

TOOL CASE

SOCKET
WRENCH

HEXAGON
WRENCH

T-TYPE
WRENCH

SPANNER
OFFSET WRENCH

SCREWDRIVER

BIT

ADJUSTABLE
WRENCH
PLIERS

SPECIALIZED
CAR EQUIPMENT

CYCLE TOOL

LED LIGHT

OTHER HAND
TOOLS

TORQUE
WRENCH

AIR TOOL