

IMPACT SOCKET ADAPTOR

Models	Square Drive (mm)	Dimensions (mm)			Qty./Carton		Weight (g)
		D	L ₁	L	(Generally)	(Store Center)	
※1 NA64	19.0 Concave × 12.7 Convex	38	25	48	5	5	216
NA68	19.0 Concave × 25.4 Convex	38	25	60	5	5	330




※ This product is patent registered.

※ In case of out-of-stock, the impact socket will be automatically changed to double-grooved type.

Pin/O-ring compatible chart

Models NA	64, 68
Pin	P4033S
O-ring	RAS322S

※ Within a plastic bag (10 pcs./pkg.)



Used to change drive size.
Electroless nickel plating.
Better appearance and anti-rust.



NA64



NA68

CAUTION

- Do not apply excessive force in case of adaptor (※1) having large concave sq. drive, as convex sq. drive might be broken.
- Limit-torque of adaptor is based on smaller sq. drive.
- Do not assemble multiple attachments. (Extension bar, Universal joint, Socket adaptor, Quick adaptor)

IMPACT SOCKET (6pt.)

Models	Across Flat (mm)	Dimensions (mm)					Qty./Carton		Weight (g)
		S	D1	D2	L1	L	d	(Generally) (Store Center)	
8NV-17	17	33.0	48	13.0	58	14	5	5	462
8NV-19	19	33.5	48	14.0	58	16	5	5	453
8NV-21	21	36.0	48	15.0	58	18	5	5	461
8NV-22	22	37.5	48	15.0	58	18	5	5	471
8NV-23	23	39.0	48	15.0	58	20	5	5	476
8NV-24	24	40.0	48	17.0	58	20	5	5	478
8NV-26	26	42.5	48	17.0	58	22	5	5	487
8NV-27	27	45.0	48	17.0	58	22	5	5	509
8NV-28	28	48.0	48	17.0	58	22	5	5	539
8NV-29	29	48.0	48	17.0	58	22	5	5	532
8NV-30	30	49.0	50	17.0	58	25	5	5	530
8NV-32	32	52.5	50	21.0	65	25	5	5	645
8NV-33	33	53.0	50	23.0	65	25	5	5	636
8NV-34	34	54.0	50	23.0	65	25	5	5	645
8NV-35	35	55.0	52	23.0	65	25	5	5	655
8NV-36	36	57.0	54	23.0	65	30	5	5	666
8NV-38	38	58.0	55	25.0	70	30	5	5	730
8NV-41	41	62.0	55	25.0	70	35	5	5	765
8NV-46	46	69.0	55	27.0	75	35	5	5	982
8NV-50	50	74.0	55	30.0	78	38	3	3	1,073
8NV-54	54	78.0	55	30.0	78	41	3	3	1,131
8NV-55	55	80.0	55	30.0	78	41	3	3	1,189
8NV-58	58	84.0	55	30.0	78	—	2	2	1,241
8NV-60	60	87.0	55	30.0	80	—	2	2	1,361
8NV-63	63	90.0	60	36.5	82	—	2	2	1,383
8NV-65	65	90.0	60	38.5	85	—	2	2	1,660
8NV-67	67	97.0	60	38.5	87	39	2	2	1,943
8NV-70	70	100.0	60	41.5	90	—	2	2	1,805
8NV-71	71	101.0	60	42.0	90	39	1	1	1,855
8NV-75	75	104.0	60	42.0	95	39	1	1	2,162
8NV-77	77	107.0	60	43.0	97	39	1	1	2,312
8NV-80	80	111.0	60	43.0	100	39	1	1	2,541
8NV-85	85	118.0	60	46.0	105	39	1	1	2,963
8NV-90	90	124.0	60	49.0	110	39	1	1	3,338
8NV-95	95	130.0	60	52.0	115	39	1	1	3,831

6-Point Strong Drive (to 8NV-17 - 50)

※ This product is patent registered.


※ In case of out-of-stock, the impact socket will be automatically changed to double-grooved type.



Electroless nickel plating.
Better appearance and anti-rust.



8NV-58



Pin/O-ring compatible chart

Models 8NV-	17 ~ 95
Pin	P4040S
O-ring	RAS326S

※ Within a plastic bag (10 pcs./pkg.)

For impact

19.0

25.4

STAINLESS TOOL
TITANIUM TOOL

TOOL SET

TOOL CASE

SOCKET
WRENCH

HEXAGON
WRENCH

T-TYPE
WRENCH

SPANNER
OFFSET WRENCH

SCREWDRIVER

BIT

ADJUSTABLE
WRENCH
PLIERS

SPECIALIZED
CAR EQUIPMENT

CYCLE TOOL

LED LIGHT

OTHER HAND
TOOLS

TORQUE
WRENCH

AIR TOOL



For impact wrenches

WARNING

- Use right size o-ring and pin securely fixed.
- O-ring and pin are consumptive parts. Replace those which are deteriorated or worn.