

Specialized socket for tightening/loosening bolts that fix the cylinder block and gasket of the engine, cylinder head.

sq.dr
12.7
mm
1/2"

12



AD402

sq.dr
12.7
mm
1/2"

sq.dr
19.0
mm
3/4"



4AD-12X

6AD-14X

Example



HEAD BOLT SOCKET SET (for Cylinder Head)

Models **AD402**

Contents **2 Items**

Models	4AD-10X	10X	12X
Across Flat (mm)		10	12

- Packaged in a plastic case
- Weight : 0.64kg
- Qty./Carton : 1




HEAD BOLT SOCKET SET (for Cylinder Head)

Models	Across Flat (mm)		Dimensions (mm)					Qty./Carton (Generally)	Weight (g)
	S	D ₁	D ₂	A	L	L ₁			
4AD-10X	10	17	24	16	200	10		10	310
4AD-12X	12	20	24	16	200	11		10	320
6AD-14X	14	23	38	25	140	12		5	550

※ Square Drive of 4AD-10X and 4AD-12X is 12.7mm.

※ Square Drive of 6AD-14X is 19.0mm.



Pin/O-ring compatible chart

Models	6AD-14X
Pin	PIN5033S
O-ring	RINGT32RS

※ Within a plastic bag (10 pcs./pkg.)

Specialized socket for tightening/loosening bolt of iron disc (flywheel) that attached to the rear end of the crankshaft.

sq.dr
19.0
mm
3/4"

12



AD604



6AD-17L

HEAD BOLT SOCKET SET (for Cylinder Head)

Models **AD604**

Contents **4 Items**


Models	6AD-14X	17L	19L	22L
	For head bolt	Head bolt and flywheel socket		
Across Flat (mm)	14	17	19	22

- Package size : w195x d100x h40mm
- Weight : 1.9kg
- Qty./Carton : 1



SOCKET for FLY WHEEL

Models	Across Flat (mm)		Dimensions (mm)				Qty./Carton (Generally)	Weight (g)
	S	D ₁	D ₂	L	L ₁			
6AD-17L	17	27	38	100	14		5	420
6AD-19L	19	29	38	100	14		5	440
6AD-22L	22	33	38	100	15		5	490



Pin/O-ring compatible chart

Models	6AD-17L ~ 22L
Pin	PIN5033S
O-ring	RINGT32RS

※ Within a plastic bag (10 pcs./pkg.)



- Use right size o-ring and pin securely fixed.
- O-ring and pin are consumptive parts. Replace those which are deteriorated or worn.