



EAN:	4013288180377	Size:	245x95x30 mm
Part number:	05073544001	Weight:	620 g
Article number:	3950/9 Hex-Plus Stainless 1 SB	Country of origin:	CZ
		Customs tariff number:	82041100

- Solution to the extraneous rust problem: fasten stainless screws with stainless tools
- Hex-Plus allows socket head screws to live longer
- Stainless L-keys prevent extraneous rust on stainless screws
- L-keys are quickly to hand thanks to their size markings
- Wear-resistant clip material for enhanced durability

High quality L-key set out of stainless steel for hexagon socket screws by Wera. Stainless steel prevents the transfer of extraneous rust. The Hex-Plus profile offers a greater contact surface in the head of the screw. The notching effect is therefore reduced to a minimum and damage to the screw head more or less eliminated. Come with hex ballpoint on the long arm: the ballpoint drive profile means that it is possible to swivel the tool axis away from the screwdriving axis, thus enabling "round the corner" screwdriving. In an almost wear-free L-key clip fastener.

Web link

https://products.wera.de/en/l-keys_l-keys_for_hexagon_socket_screws_3950_9_hex-plus_stainless_1_sb.html

Wera - 3950/9 Hex-Plus Stainless 1 SB
05073544001 - 4013288180377

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

L-Keys for Hexagon Socket Screws

L-Keys



We questioned the classic L-key design, since all too often the screw head recess is rounded out, meaning screws can no longer be tightened or loosened - and so the user finds the L-key slipping out of the recess. Wera Hex-Plus tools have a larger contact surface in the screw head. The notching effects are reduced and thereby the deformation of the screws. At the same time, as much as 20 % more torque can be applied.

Stainless L-keys



Stainless L-keys are hardened to the same strength as conventional (carbon) steel tools, and prevent extraneous rust forming.

Vacuum ice-hardened



The stainless steel tools from Wera are vacuum ice-hardened and have the hardness and strength needed for screw connections. There are no limitations to the industrial applications they are suitable for.

Hex-Plus



Hexagon screws can endure a problem because the contact surfaces delivering the power from the conventional tool, is transferred to the screw via very small surface areas. The consequence: the screw can become damaged (rounding out). Hex-Plus tools have a greater contact surface that prevents this from happening! At the same time, as much as 20 % more torque can be applied. Good to know: Hex-Plus tools fit into every standard hexagon socket screw!

Ball tip



The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, "around-the-corner" screwdriving jobs.

Size identification



The size of each L-key has been engraved by a laser. In addition Take it easy L-keys have a colour coding according to sizes - for simple and rapid accessing of the required tool. Making it easy to find the right tool.

Secure hold and easy removal



The wear-resistant clip material ensures that the L-keys are securely held yet are easy to remove.

Web link

https://products.wera.de/en/l-keys_l-keys_for_hexagon_socket_screws_3950_9_hex-plus_stainless_1_sb.html

Wera - 3950/9 Hex-Plus Stainless 1 SB
05073544001 - 4013288180377

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

L-Keys for Hexagon Socket Screws

Set contents:

3950 PKL L-key, metric, stainless, 1.5 x 90 mm



05022700001	1x	1.5 x 90 mm
05022701001	1x	2 x 101 mm
05022702001	1x	2.5 x 112 mm
05022703001	1x	3 x 123 mm
05022704001	1x	4 x 137 mm
05022705001	1x	5 x 154 mm
05022706001	1x	6 x 172 mm
05022708001	1x	8 x 195 mm
05022709001	1x	10 x 224 mm

Web link

https://products.wera.de/en/l-keys_l-keys_for_hexagon_socket_screws_3950_9_hex-plus_stainless_1_sb.html

Wera - 3950/9 Hex-Plus Stainless 1 SB
05073544001 - 4013288180377

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de