POWER TOOLS & ABRASIVES

MAKITA POWER TOOLS เครื่องมือไฟฟ้า "มากีต้า"



HW1200

High Pressure Washer

12 MPa (120 Bar) High Pressure Washer with Self-Priming Function



HW1300

High Pressure Washer

13 MPa (130 Bar) High Pressure Washer with Self-Priming Function



VC2510L

Vacuum Cleaner



Continuous rating Input

1,800W 12 Mpa (120 bar, 1,740 PSI) 420 L/h 40°C (104°F) 10 m (33 ft.) 292 x 358 x 830 mm (11-1/2 x 14-1/8 x 32-3/4°) 11 kg (24.3 lbs.) 5.0 m (16.4 ft)

Continuous rating Input Max Pressure Max Flow Rate Max Feed Temperature High Pressure Hose Length Dimensions (L x W x H) Net weight Power supply cord

1,800W 13 Mpa (130 bar, 1,885 PSI) 450 L/h 40°C (104°F) 10 m (33 ft.) 292 x 358 x 830 mm (11-1/2 x 14-1/8 x 32-3/4") 12.7 kg (28 lbs.) 5.0 m (16.4 ft)

GYUPFA!!

173 MW 🕸 💥 🔀

Continuous rating Input Max peak air flow Max Sealed Suction (water column) Tank Capacity

Dimensions (L x W x H) Net weight Power supply cord

1,050W 2.0 m³ / min 22.0 kPa (2,240 mmH₂O)

Dust: 25 L Water: 14 L 432 x 416 x 451 mm (17 x 16-3/8 x 17-3/4") 10.5 kg (23.2 lbs.) 5.0 m (16.4 ft)

VC3210L

Net weight Power supply cord

Vacuum Cleaner

32 L Dust Class L GYUPPA Vacuum



VC3211H

Vacuum Clean

32 L Dust Class H GYUPPA Vacuum



EK6100 305 mm (12")



GYNFFIL!

Continuous rating Input (water column) Tank Capacity Dimensions (L x W x H) Net weight Power supply cord

2.0 m³ / min 22.0 kPa (2,240 mmH₂O)

Dust: 32 L Water: 27 L 552 x 398 x 685 mm (21-3/4 x 15-5/8 x 27") 14.5 kg (32 lbs.) 5.0 m (16.4 ft) GYNFAN!

173 MW 🕸 🗁 🔀

Continuous rating Input Max peak air flow Max Sealed Suction (water column) (water column Tank Capacity

Dimensions (L x W x H) Net weight Power supply cord

2 m³ / min 22.0 kPa (2,240 mmH₂O)

Water: 27 L 552 x 398 x 685 mm (21-3/4 x 15-5/8 x 27") 16.9 kg (37.3 lbs.) 5.0 m (16.4 ft)

Wheel Diameter 305 mm (12") 305 mm (12") 61 mL 1100 mm (4-5/16") 5100 80 m/s 3.2 kW / 4.4 PS 0.7 L 97 dB(A) 113 dB(A) 28 m/s² Engine
Max cutting depth
No Load Speed (RPM)
Circumferential speed Circumferential speed Engine power Fuel Tank Capacity Sound Pressure Level Sound Power Level Vibration Level Front Grip Vibration Level Rear Grip Overal Length Net weight 675 mm (26-1/2" 8.5 kg (18.7 **l**bs.)

EK6101

355 mm (14")



305 mm (12")

EK7650H





EK7651H 355 mm (14")

Wheel Diameter Engine Max cutting depth No Load Speed (RPM) Circumferential speed Engine power Fuel Tank Capacity Sound Pressure Level Sound Power Level Vibration Level Front Grip Vibration Level Rear Grip Overall Length Net weight Wheel Diameter

355 mm (14") 61 mL 130 mm (5-1/8") 4,400 80 m/s 3.2 kW / 4.4 PS 0.7 L 100 dB(A) 109 dB(A) 2.7 m/s² 3.5 m/s²

MM4

Pe CDI 🐌

305 mm (12")

Wheel Diameter 305 mm (12") 75.6 mL 97 mm (3-13/16") 4,300 80 m/s 92.7 dB(A) 104.6 dB(A) 2.7 m/s² 1.8 m/s² 1.1 L Max cutting depth
No Load Speed (RPM)
Circumferential speed
Engine power
Sound Pressure Level Sound Pressure Level
Sound Power Level
Vibration Level Front Grip
Vibration Level Rear Grip
Fuel Tank Capacity
Dimensions (L x W x H)
Net weight

761x310x435 mm(30"x12-1/4"x17-1/18") 14 kg (31 lbs.)

MM4}

Wheel Diameter Engine Max cutting depth No Load Speed (RPM) Circumferential speed Engine power Fuel Tank Capacity Sound Pressure Level Sound Power Level John Sound Pressure Level Front Grip Vibration Level Front Grip Dibration Level Rear Grip Dimensions (L x W x H) Net weight Wheel Diameter

355 mm (14") 75.6 mL 122 mm (4-13/16") 4,300 80 m/s 3.0 kW / 4.1 PS 1.1 L 92.7 dB(A) 104.6 dB(A) 2.7 m/s² 1.8 m/s²

355 mm (14")

780x310x455 mm (30-3/4"x12-1/4"x17-7/8") 14.2 kg (31.3 lbs.)

EK8100



Net weight: without blade and fuel. Trolley and foot with wheels are available as option.

Whee**l** Diameter 405 mm (16") Engine Max cutting depth Circumferential speed 81 mL 147 mm (5-3/4") 147 mm (5-3/4") 80 m/s 4.2 kW / 5.6 PS 1.1 L 100.3 dB(A) 109.6 dB(A) 7.8 m/s² 6.1 m/s² 830 mm (32-3/4") 10.6 kg (23.4 lbs.) Circumterential speed Engine power Fuel Tank Capacity Sound Pressure Level Sound Power Level Vibration Level Front Grip Vibration Level Rear Grip Overal Length Net weight

MUH355G

Hedge Trimmer



Continuous rating Input Blade length Dimensions (L x W x H) Net Weight Electrics wire 350 mm 560x175x165 mm UH3502

Hedge Trimme



Continuous rating Input Blade length Dimensions (L x W x H) Net Weight Electrics wire 320 W 350 mm 660x175x165 mm 1.8 kg 3.0 m

