L-shaped

Manufactured from high alloy steel, which offers high torque, durability, and abrasion resistance. Heat-treated alloy steel and hard chrome plating provide high strength and resistance, increasing work efficiency and safety.

BS900

STAINLESS TOOL TITANILIM TOOL

TOOL SET

TOOL CASE

SOCKET WRENCH

HEXAGON WRENCH

T-TYPF WRENCH

SPANNER OFFSET WRENCH

SCREWDRIVER

ADJUSTABLE WRENCH

PLIERS

SPECIALIZED CAR FOLEPMENT

CYCLE TOOL

LED LIGHT

OTHER HAND TOOLS

TOROUF

AIR TOOL

Ball-pointed design allows quick-turning and temporary

tightening. MASTERTOOL **Special alloy steel** Model change



BALL POINT HEX KEY WRENCH SET L-TYPE

BS900 Models

Contents 9 Items

ModelsBS-1.5 02 2.5 03 04 10 05 06 Across Flat(mm) 1.5 2 2.5 3 4 5 6 8 10

With a holder • Weight: 0.31kg

• Qty./Carton : 6



BALL POINT HEX KEY WRENCH L-TYPE

Models	Across Flat (mm)	Dimensions (mm)		Qty./Carton	Weight (g)
		Н	L		(6)
BS-1.5	1.5	14	51	6	1
BS-02	2	16	58	6	2
BS-2.5	2.5	18	65	6	3
BS-03	3	20	74	6	6
BS-04	4	25	78	6	11
BS-05	5	28	89	6	19
BS-06	6	32	101	6	32
BS-08	8	36	112	6	63
BS-10	10	40	128	6	113






Manufactured from high alloy steel, which offers high torque, durability, and abrasion resistance. Heat-treated alloy steel and hard chrome plating provide high strength and resistance, increasing work efficiency and safety.

Ball-pointed design allows quick-turning and temporary





Short-neck part is very useful for using at a narrow place.



For ball point type, it can be tilting until 30 degree



SHORT NECK BALL POINT HEX KEY WRENCH SET L-TYPE

BS900S Models

Contents 9 Items

Models BS-1.5S 02S 2.5S 03S **04S 05S** 06S 08S 10S Across Flat(mm) 1.5 2 2.5 3 4 5 6 8 10

• With a holder Weight : 0.26kg

• Qty./Carton : 6



SHORT NECK BALL POINT HEX KEY WRENCH L-TYPE

Models	Across Flat (mm)	Dimensions (mm)		Qty./Carton	Weight (g)
		Н	L		(3)
BS-1.5S	1.5	4	51	6	1
BS-02S	2	5	58	6	2
BS-2.5S	2.5	6	65	6	3
BS-03S	3	8	74	6	5
BS-04S	4	9	78	6	10
BS-05S	5	11	89	6	16
BS-06S	6	13	101	6	27
BS-08S	8	16	112	6	55
BS-10S	10	18	128	6	98







