

เอกสารข้อมูลผลิตภัณฑ์

ข้อมูลจำเพาะ



APC Easy UPS On-Line, 6kVA/6kW, Rackmount 2U, 230V, 1x Hard wire 3-wire(1P+N+E) outlet, Intelligent Slot, Extended runtime, No battery, W/O rail kit

SRVPM6KRIL

Overview

Presentation	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	6000 W
rated power in VA	6000 VA
Output connector type	Hard wire 3-wire (1P + N + E) 1
Number of rack unit	2U
Provided equipment	1 USB cable 1 RS-232 configuration cable 1 rack mounting brackets 1 stabilization/wall mounting feet 1 battery cable user manual
Range of product	Easy UPS On-Line

Batteries & Runtime

ประสิทธิภาพ	View Efficiency Graph
Battery type	External battery system
Battery voltage	240 V
Extended runtime	1
Number of battery filled slots	0
Number of battery free slots	0
Battery charger power	1170 W rated

General

Number of power module filled slots	0
-------------------------------------	---

การส่งสิทธิ์: เอกสารนี้ไม่มีวัตถุประสงค์เพื่อใช้แทน หรือใช้เพื่อกำหนดความเหมาะสม หรือความน่าเชื่อถือของผลิตภัณฑ์เหล่านี้สำหรับการใช้งานเฉพาะทาง

Number of power module free slots	0
Redundant	No

Physical

Colour	Black (RAL 7010)
Height	8.65 cm
Width	43.8 cm
Depth	61.5 cm
Net weight	14 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted with kit
USB compatible	No
Mounting position	Horizontal

Input

Input voltage limits	110...300 V 60 % load 176...300 V full load
Number of input connectors	1 hard wire 3-wire (1P + N + E)
Network frequency	40...70 Hz auto sensing

Output

Maximum configurable power in VA	6000 VA
Maximum configurable power in W	6000 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Harmonic distortion	1 %
UPS type	Double conversion online
Wave type	Sine wave
Efficiency	94 % (full load)
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1

Conformance

Product certifications	CE EAC
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m

Ambient air temperature for storage	-15...60 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...15000 m
Acoustic level	55 dBA
Heat dissipation	1172 Btu/h
IP degree of protection	IP20

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Yes
Free slots	1

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24 cm
Package 1 Width	60 cm
Package 1 Length	76 cm
Package 1 Weight	18 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

ชไนเดอร์ อิเล็คทริคมีเป้าหมายที่จะบรรลุสถานะ Net Zero ภายในปี 2050 ด้วยความร่วมมือในห่วงโซ่อุปทาน วัสดุที่มีผลกระทบต่ำลง และการหมุนเวียนผ่านแคมเปญ "Use Better, Use Longer, Use Again" เพื่อยืดอายุการใช้งานของผลิตภัณฑ์และการนำกลับมาใช้ใหม่

Environmental Data คืออะไร >

วิธีประเมินความยั่งยืนของผลิตภัณฑ์ >

🌱 พุดพริ้นต์ด้านสิ่งแวดล้อม	
Environmental Disclosure	Product Environmental Profile
Use Better	
📦 วัสดุและสาร	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACH Regulation	REACH Declaration
Use Again	
♻️ บรรจุและผลิตใหม่	
Circularity Profile	End of Life Information
Take-back	No

Image of product / Alternate images

Alternative

