

เอกสารข้อมูลผลิตภัณฑ์

ข้อมูลจำเพาะ



APC Easy UPS, 900VA, Tower, 230V, 2 Universal + 1 IEC C13 outlets, AVR

BVX900LI-MS

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	230 V AC 1 phase
Main Output Voltage	230 V AC 1 phase
Rated power in W	480 W
rated power in VA	900 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 60320 C14
output connection type	2 universal 1 IEC 60320 C13
Cable length	1.2 m
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	User manual
Range of product	Easy UPS

Batteries & Runtime

รันไทม์	View Runtime Graph
ประสิทธิภาพ	View Efficiency Graph
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Battery voltage	12 V
Battery capacity	9.0 Ah
Battery life	2...3 year(s)
Replacement battery	RBC17
Extended runtime	0

General

Max runtime	120 min
Number of power module free slots	0

การละสิทธิ์: เอกสารนี้ไม่มีวัตถุประสงค์เพื่อใช้แทน หรือใช้เพื่อกำหนดความเหมาะสม หรือความน่าเชื่อถือของผลิตภัณฑ์เหล่านี้สำหรับการใช้งานเฉพาะทาง

Number of power module filled slots	0
Redundant	No
UPS size	WS

Physical

Colour	Black
Height	16 cm
Width	12 cm
Depth	35.5 cm
Net weight	6 kg
Mounting support	Floor
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	140...300 V 230 V AC
Cos phi	0.53

Output

Maximum configurable power in W	480 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Full load runtime	00:01:00 480 W
Graph display	1
Half load runtime	00:06:30 240 W
Maximum configurable power in VA	900 VA
Transfer time	6 ms typical : 10 ms maximum

Conformance

Product certifications	CE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m

Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...3000 m
Acoustic level	40 dBA
IP degree of protection	IP20

Surge Protection and Filtering

Surge energy rate	273 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25 cm
Package 1 Width	43 cm
Package 1 Length	19.7 cm
Package 1 Weight	6.5 kg
SCC14	10731304404368

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

ชไนเดอร์ อิเล็คทริคมีเป้าหมายที่จะบรรลุสถานะ Net Zero ภายในปี 2050 ด้วยความร่วมมือในห่วงโซ่อุปทาน วัสดุที่มีผลกระทบต่ำลง และการหมุนเวียนผ่านแคมเปญ "Use Better, Use Longer, Use Again" เพื่อยืดอายุการใช้งานของผลิตภัณฑ์และการนำกลับมาใช้ใหม่

Environmental Data คืออะไร >

วิธีประเมินความยั่งยืนของผลิตภัณฑ์ >

🌱 ฟุตพริ้นต์ด้านสิ่งแวดล้อม	
Environmental Disclosure	Product Environmental Profile
Use Better	
📦 วัสดุและสาร	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	E7333b0a-8d2c-4a40-a279-6eb5db3419eb
REACH Regulation	REACH Declaration
Use Again	
♻️ บรรจุและผลิตใหม่	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	No
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative



