



Rack PDU,Basic, 1U, 16A,
208&230V, (10)C13 & (2)C19



AP9559

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	2.5 m
Number of cables	1
Provided equipment	User manual Rack mounting brackets

Complementary

Input Voltage	120 V 208 V 230 V
Height	4.4 cm
Width	44.7 cm
Output Voltage	120 V 208 V 230 V
Depth	5.7 cm
Net weight	0.98 kg
Mounting location	Front Rear
Mounting preference	No preference
Input Plug Type	IEC 60320 C20
Mounting mode	Rack-mounted
Rack units	1U
Mounting position	Horizontal
Permissible voltage	90...250 V
Max line current	16 A
Input current limits	16 A
Load capacity	3680 VA
Network frequency	50/60 Hz

การละสิทธิ: เอกสารนี้ไม่มีวัตถุประสงค์เพื่อใช้แทน หรือใช้เพื่อกำหนดความเหมาะสม หรือความเข้ากันได้ของผลิตภัณฑ์เหล่านี้สำหรับการใช้งานเฉพาะทาง

Outlet type and quantity	10 IEC 60320 C13 2 IEC 60320 C19
--------------------------	-------------------------------------

Environment

Product certifications	cUL listed CE UL listed VDE Victoria
Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...15240.0000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.5 cm
Package 1 Width	48.3 cm
Package 1 Length	15.2 cm
Package 1 Weight	2.355 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Schneider Electric has a commitment to achieving Net Zero by 2050 with the help of our stakeholders. We have a goal to reduce our carbon footprint and to use better, longer, and again. We encourage our customers to use our products and services to reduce their carbon footprint and to use better, longer, and again.

Environmental Data คืออะไร >

วิธีประเมินความยั่งยืนของผลิตภัณฑ์ >

ฟุตพริ้นต์ด้านสิ่งแวดล้อม	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	29
Environmental Disclosure	Product Environmental Profile

Use Better

วัสดุและสาร	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACH Regulation	REACH Declaration
Halogen content performance	Product contains halogen above thresholds

มีประสิทธิภาพพลังงาน	
Optimized Energy Efficiency	Energy efficient product

Use Again

บรรจุและผลิตใหม่	
Circularity Profile	End of Life Information
Take-back	Yes
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

