

เอกสารข้อมูลผลิตภัณฑ์

ข้อมูลจำเพาะ



Power Cord Kit (6 ea), Locking, C19 to C20, 0.6m

AP8712S

Overview

Presentation	Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.
Lead time	Usually in Stock

Main

Product or component type	Power cord
Input Connection Type	IEC 60320 C20
Cable length	0.6 m
Number of cables	6

Physical

Colour	Black
Height	30 cm
Width	6 cm
Depth	6.5 cm
Net weight	1.12 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Max line current	16 A
Input current limits	16 A

Output

Max current draw	16 A
Number of power socket outlets	1 IEC 60320 C19
Power cable length	0.6 m

Conformance

การละเมิดลิขสิทธิ์: เอกสารนี้ไม่มีวัตถุประสงค์เพื่อใช้แทน หรือใช้เพื่อกำหนดความเหมาะสม หรือความน่าเชื่อถือของผลิตภัณฑ์เหล่านี้สำหรับการใช้งานเฉพาะทาง

Product certifications	CCC CSA PSE UL listed VDE
------------------------	---------------------------------------

Environmental

Ambient air temperature for operation	0...75 °C
Relative humidity	20...80 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...75 °C
Storage Relative Humidity	20...80 %
Storage altitude	0.0000000000...15240.0000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30 cm
Package 1 Width	6 cm
Package 1 Length	6.5 cm
Package 1 Weight	1.12 kg
SCC14	10731304279683

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

ชาไนเตอร์ อิเล็กทรอนิกส์เป้าหมายที่จะบรรลุสถานะ Net Zero ภายในปี 2050 ด้วยความร่วมมือในห่วงโซ่อุปทาน วัสดุที่มีผลกระทบต่อสิ่งแวดล้อม และการหมุนเวียนผ่านแคมเปญ "Use Better, Use Longer, Use Again" เพื่อยืดอายุการใช้งานของผลิตภัณฑ์และการนำกลับมาใช้ใหม่

Environmental Data คืออะไร >

วิธีประเมินความยั่งยืนของผลิตภัณฑ์ >

🌱 ฟุตพริ้นต์ด้านสิ่งแวดล้อม	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	352
Environmental Disclosure	Product Environmental Profile

Use Better

♻️ วัสดุและสาร	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACH Regulation	REACH Declaration
Halogen content performance	Product contains halogen above thresholds

Use Again

🔄 บรรจุและผลิตใหม่	
Circularity Profile	End of Life Information
Take-back	Yes
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins