



Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 11.0kW, 230V, (21) C13 & (3) C19

AP8681

Overview

Presentation	APC Metered by Outlet with Switching Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and individual outlet power metering. Remote outlet level controls allow power on/off functionality for power recycling to reboot locked-up equipment and to avoid unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, and locking IEC receptacles. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.
Lead time	Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Switched metered outlet
Cord length	1.8 m
Provided equipment	CAN port terminator Installation guide Rack mounting brackets Safety guide Serial configuration cable

Complementary

Input Voltage	400 V 3 phases
Height	182.9 cm
Width	5.6 cm
Output Voltage	230 V
Depth	5.1 cm
Net weight	8.23 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 16 A 3P + N + PE IEC 60309 20 A 3P + N + PE
Mounting mode	Rack-mounted
Rack units	0U

การละสิทธิ์: เอกสารนี้ไม่มีวัตถุประสงค์เพื่อใช้แทน หรือใช้เพื่อกำหนดความเหมาะสม หรือความเข้ากันได้ของผลิตภัณฑ์เหล่านี้สำหรับการใช้งานเฉพาะทาง

Mounting position	Vertical
[In] rated current	16 A
Max line current	16 A
Input current limits	16 A
Load capacity	11000 VA
Network frequency	50/60 Hz
Outlet type and quantity	21 IEC 60320 C13 3 IEC 60320 C19

## Environment

Product certifications	cUL listed UL listed VDE
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 FCC part 15 class A ICES-003
Ambient air temperature for operation	-5...60 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Storage Relative Humidity	5...95 %
Storage altitude	0.0000000000...15240.0000000000 m

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	203.8 cm
Package 1 Width	16.2 cm
Package 1 Length	11.7 cm
Package 1 Weight	10.478 kg

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Environmental Data

ชไนเดอร์ อิเล็คทริคมีเป้าหมายที่จะบรรลุสถานะ Net Zero ภายในปี 2050 ด้วยความร่วมมือในห่วงโซ่อุปทาน วัสดุที่มีผลกระทบต่ำลง และการหมุนเวียนผ่านแคมเปญ "Use Better, Use Longer, Use Again" เพื่อยืดอายุการใช้งานของผลิตภัณฑ์และการนำกลับมาใช้ใหม่

Environmental Data คืออะไร >

วิธีประเมินความยั่งยืนของผลิตภัณฑ์ >


🌱 <b>ฟุตพริ้นต์ด้านสิ่งแวดล้อม</b>	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	10364
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
<b>Use Better</b>	
♻️ <b>วัสดุและสาร</b>	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
<a href="#">EU RoHS Directive</a>	Compliant with Exemptions
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACH Regulation	<a href="#">REACH Declaration</a>
Halogen content performance	Product contains halogen above thresholds
🔋 <b>มีประสิทธิภาพพลังงาน</b>	
Optimized Energy Efficiency	Energy efficient product
<b>Use Again</b>	
🔄 <b>บรรจุและผลิตใหม่</b>	
Circularity Profile	<a href="#">End of Life Information</a>
Removable battery	Yes
Take-back	Yes
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

---

