

เอกสารข้อมูลผลิตภัณฑ์

ข้อมูลจำเพาะ



APC Smart-UPS C, Line Interactive, 1000VA, Tower, 230V, 8x IEC C13 outlets, SmartConnect port, USB and Serial communication, AVR, Graphic LCD

SMC1000IC

Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually in Stock

Main

Product or component type	Uninterruptible power supply (UPS)
---------------------------	------------------------------------

Complementary

Communication port type	SmartConnect Ethernet port
Software package	SmartConnect software for remote power monitoring feature availability varies by terms of use

Batteries & Runtime

รุ่นใหม่	View Runtime Graph
ประสิทธิภาพ	View Efficiency Graph
Battery type	Lead-acid battery
Battery voltage	24 V
Extended runtime	0
Battery capacity	9 Ah
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	3...5 year(s)
Replacement battery	APCRBC142
Battery charger power	56 W rated

General

Provided equipment	Power cord USB cable
Number of power module	0

การละสิทธิ์: เอกสารนี้ไม่มีวัตถุประสงค์เพื่อใช้แทน หรือใช้เพื่อกำหนดความเหมาะสม หรือความน่าเชื่อถือของผลิตภัณฑ์เหล่านี้สำหรับการใช้งานเฉพาะทาง

Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	Cloud-enabled monitoring
Redundant	No

Physical

Colour	Black
Height	21.9 cm
Width	17.1 cm
Depth	43.9 cm
Net weight	17.27 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes

Input

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Input Connection Type	IEC 320 C14
Input voltage limits	170...300 V adjustable 180...287 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	600 W
rated power in VA	1000 VA
output connection type	8 IEC 60320 C13
Harmonic distortion	Less than 5 %
Maximum configurable power in VA	1000 VA
Maximum configurable power in W	600 W
Transfer time	6 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product certifications	CE GOST VDE UK PSTI
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Acoustic level	41 dBA
Heat dissipation	100 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.0000000000...15240.0000000000 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

control panel	Multifunction LCD status and control console
Free slots	0
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rate	455 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	37.6 cm
Package 1 Width	59.5 cm
Package 1 Length	32.8 cm
Package 1 Weight	19.55 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

ชไนเดอร์ อิเล็คทริคมีเป้าหมายที่จะบรรลุสถานะ Net Zero ภายในปี 2050 ด้วยความร่วมมือในห่วงโซ่อุปทาน วัสดุที่มีผลกระทบต่ำลง และการหมุนเวียนผ่านแคมเปญ "Use Better, Use Longer, Use Again" เพื่อยืดอายุการใช้งานของผลิตภัณฑ์และการนำกลับมาใช้ใหม่

Environmental Data คืออะไร >

วิธีประเมินความยั่งยืนของผลิตภัณฑ์ >

🌱 ฟุตพริ้นต์ด้านสิ่งแวดล้อม	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	854
Environmental Disclosure	Product Environmental Profile

Use Better

♻️ วัสดุและสาร	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	B2b22a56-41f2-497e-9ea6-cf093b3b8bd3
REACH Regulation	REACH Declaration

💡 มีประสิทธิภาพพลังงาน	
Optimized Energy Efficiency	Energy efficient product

Use Again

♻️ บรรจุและผลิตใหม่	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes

Image of product / Alternate images

Alternative



